

# SET-UP SHEET

# XRAY XB4'23

RACE	Bohumin cup R2	
TRACK	Bohumin	
NAME	Max	DATE 9.12.2023

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	2	FINAL POSITION	2

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH	
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 40k	OIL	OIL 20k

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T <input checked="" type="checkbox"/>	CROWN GEAR	40T <input checked="" type="checkbox"/>

CENTRAL SLIPPER & ONE-WAY SETTING	
SLIPPING ADJUSTMENT	ONE-WAY TIGHTNESS
12.9 mm	1 CCW TURN (BASIC SETUP)
LOOSE	FULLY TIGHTEN

GEARING	
PINION 18	78 CENTER DIFF SPUR

FRONT	SHOCKS	REAR
4	SPRINGS	4
350	OIL	300
%	REBOUND	%
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	ø1.2mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	ø1.3mm	<input type="checkbox"/> 6 HOLES
	ø1.4mm	
	ø1.6mm	
	ø1.7mm	
	CUSTOM PISTONS	
	ø mm 1.8 mm	

FRONT	ANTI ROLL BAR	REAR
2	THICKNESS	

FRONT	TIRES	REAR
Fusion2	BRAND	Cactus
	COMPOUND	
	INSERTS	
XRAY	WHEELS	HARD

ELECTRONICS		
MOTOR	4.5T	Nitride
MOTOR TIMING	30	LCG
BATTERY SIZE		SPEEDO
STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>		BATTERY

BODY	
TYPE	Gamma 4CL
	STANDARD <input type="checkbox"/> LIGHT <input checked="" type="checkbox"/>

COMMENTS	
Wide C/D blocks	

FRONT	APPLIED	REAR
ALU C-HUB SHIM UP 0 /mm DOWN 2 /mm LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> DRIVE SHAFT CVD <input type="checkbox"/> ECS <input checked="" type="checkbox"/> Length 83 /mm SHIM 1 mm LOWER SHOCK POSITION #10711 GAUGE	SHIM 3 mm DRIVE SHAFT Length 77 /mm SHIMS 0 /mm HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU HIGH <input type="checkbox"/> ALU LOW <input checked="" type="checkbox"/> #325341 ADJ. DRIVE AXLE 1 2 3 4 #10711 GAUGE	

FRONT	WING CUTTING LINE	WING SIDE LINE
CASTER 6° <input type="checkbox"/> 7° <input checked="" type="checkbox"/> 9° <input type="checkbox"/> 12° <input type="checkbox"/> OFFSET 3 /slots BUMP STEER SHIM 3 mm	1 2 3 4 5 OFFSET 4 /slots UPRIGHT WHEELBASE SHIM 0 /mm IN FRONT OF ARM	HIGHER <input type="checkbox"/> LOWER <input checked="" type="checkbox"/> WING POSITION UP <input checked="" type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> WING THICKNESS 0.75 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 1.5 <input type="checkbox"/> TYPE

FF	RF	RR 2°
1° <input type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>	UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>

FRONT	REAR
FRONT TOE 1 OUT STEER. PLATE HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BUMP STEER SHIM 0 mm SHIM UNDER STEER. PLATE SERVO SAVER SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT <input checked="" type="checkbox"/> MATERIAL STANDARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ARM SHIM 2 mm	REAR TOE 1.5 IN GRAPHITE FOR REAR BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> REAR BRACE MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> ARM SHIM 2 mm

FRONT	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR
FRONT CAMBER 2 DOWNSTOP SHIM 0 mm LENGTH 24 mm UPSTOP SHIM 0 mm COLLAR STANDARD <input checked="" type="checkbox"/> -2mm	FRONT DIFF HEIGHT 13 mm RIDE HEIGHT 13 mm #107720 GAUGE	REAR DIFF HEIGHT 2.5 DOWNSTOP SHIM 0 mm LENGTH 28+2 mm UPSTOP SHIM 4 mm COLLAR STANDARD <input type="checkbox"/> -2mm	REAR CAMBER DOWNSTOP SHIM 0 mm LENGTH 28+2 mm UPSTOP SHIM 4 mm COLLAR STANDARD <input type="checkbox"/> -2mm

FRONT ARMS	BALANCE	MOTOR MOUNT	BALANCE	REAR ARMS
LONG <input type="checkbox"/> SHORT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	g	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	g	LONG <input type="checkbox"/> SHORT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
CHASSIS ALU <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>				