

XRAY XB4'23

FRONT

ALU C-HUB SHIM
UP ☒ 3 /mm
DOWN ☐ 1 /mm

LONGER BUSHINGS
UP ☐
DOWN ☒

DRIVE SHAFT
CVD ☒ ECS ☐
Length 83 /mm

SHIM
2 mm

STEERING BLOCK
MEDIUM ☐
HARD ☒
GRAPHITE ☐

LOWER SHOCK POSITION

DOWNSTOP
#107711 GAUGE

HUBDY
#107701 SUPPORT BLOCKS

REAR UPRIGHT

DRIVE SHAFT
Length 77 /mm

SHIM
2 mm

SHIMS
4 /mm

HARD GRAPHITE ALU HIGH ALU LOW
☒ ☐ ☐ ☐

#325341 ADJ. DRIVE AXLE
1 2 3 4

ROLL ENTER

WING CUTTING LINE
1 2 3 4 5

OFFSET
/slots

UPRIGHT WHEELBASE
SHIM /mm

IN FRONT OF ARM

WING SIDE LINE
HIGHER ☐ LOWER ☒

WING POSITION
UP ☐
MIDDLE ☒
DOWN ☐

WING THICKNESSES
0.75 ☐ 1 ☒ 1.5 ☐

TYPE

CASTER
6° ☐
7° ☐
9° ☐
12° ☐

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☐

BUMP STEER
SHIM 2 mm

FF

FR

RF

RR2°

ROLL CENTER
ECCENTRIC BUSHINGS

UP ☐ **DOWN** ☒

FRONT TOE
OUT -2

ARM SHIM
2 mm

STEER. PLATE
HARD ☒
GRAPHITE ☐
ALU ☐

BUMP STEER
SHIM 2 mm

Servo SAVER
SOFT ☐
MEDIUM ☒
TIGHT ☐

MATERIAL
STANDARD ☒
GRAPHITE ☐

REAR TOE
3

GRAPHITE FOR REAR BRACE
YES ☒
NO ☐

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM
0 mm

FRONT CAMBER
2

DOWNSTOP
SHIM 2.5 mm

LENGTH
19 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☐ -2mm ☒

FRONT DIFF HEIGHT

RIDE HEIGHT
16.5 mm

REAR DIFF HEIGHT

RIDE HEIGHT
16.5 mm

REAR CAMBER
2

DOWNSTOP
SHIM 0 mm

LENGTH
29 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☐ -2mm ☒

FRONT ARMS
LONG ☐
SHORT ☐
MEDIUM ☐
HARD ☒
GRAPHITE ☐

BALANCE
g

MOTOR MOUNT
FRONT ☒ REAR ☐

T-BRACE

FRONT BATTERY POST

REAR BATTERY POST

CHASSIS
ALU ☒
GRAPHITE ☐

SIDE GUARDS
HARD ☒
GRAPHITE ☐

BALANCE
g

FRONT

REAR