

# SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'24

RACE	club race				
TRACK	N-control				
NAME	Ethan Lefebvre		DATE	12/10/23	
QUAL POSITION	2	FINAL POSITION	1	BEST LAPTIME	13.3 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	5	/cSt
PINION	/T	SPUR GEAR	/T	FINAL DRIVE RATIO	

FRONT	SHOCKS	REAR
2.5/2.8	XRAY SPRINGS	2.6
350	OIL /cSt	350
	REBOUND %	
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
<input checked="" type="checkbox"/> PSS	<input type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS
.8		.8
SHOCK LENGTH	/mm	SHOCK LENGTH
1.2	THICKNESS/mm	1.2

TIRES		TREATED AREA	
ADDITIONAL		ADDITIONAL	
ADDITIONAL TIMING		ADDITIONAL TIMING	
WIPE OFF TIME		WIPE OFF TIME	
TIRE WARMERS		TIRE WARMERS	
Timing:	Temp.:	Timing:	Temp.:
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT %	REAR %
MOTOR	4.5	TIMING		
ESC	HW	BATTERIES		
BODY	Special	WING	twister .6	

BODY POSITION	Dimension from body post to window bottom line
WING SIDE PLATE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
Dimension from body post to upper holder	
Dimension from edge to surface	/mm

X4'23	1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'22	2.0mm	<input type="checkbox"/> 1.6mm	
X4'22	2.0mm	<input type="checkbox"/> 1.6mm	
	NONE	<input type="checkbox"/> BEARING	

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
HEIGHT	SHIM
2 /mm	2 /mm
FF	RF
5.4 /mm	5.6 /mm
FR	RR
2 /mm	2 /mm
TOE GAIN	TOE GAIN
2.5 /mm	2.5 /mm
SERVO SAVER	SERVO HORN
<input type="checkbox"/>	<input checked="" type="checkbox"/>

FRONT	
CAMBER	2 /deg. Left=Right
BODY STOP	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
SHOCK HOLDERS	SHIM 4 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	58mm 59mm BEARING BLADE
FRONT HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM	.5 /mm
DOWNSTOP	/mm

REAR	
CAMBER	2 /deg. Left=Right
BODY POST	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS	SHIM 4 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	52mm 54mm BEARING BLADE
REAR HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM	.5 /mm
DOWNSTOP	/mm

FRONT TOP VIEW		REAR TOP VIEW	
TOE OUT	1 /deg. Left=Right	TOE IN	3 /deg. Left=Right
ACKERMANN	SHIM .5 /mm	SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING	SHIM 0 /mm
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW		REAR BOTTOM VIEW	
STEER. LOCK	26.5 /deg.	T-BRACE	ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER	FR RE	CHASSIS T-BRACE	
FRONT ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
CHASSIS	GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm		