

# SET-UP SHEET

XB2'24 SET-UP SHEET VER. 1 ©XRAY 2023

**XRAY XB2'24**

RACE	XRS R5	
TRACK	HudyArena	
NAME	Max	DATE 2024-02-11

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	4	FINAL POSITION	4

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM
TRACTION	<input type="checkbox"/> VERY-LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> VERY-HIGH	
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY

TRANSMISSION		
BALL DIFF	<input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
DIFFERENTIAL	OIL 100k cSt	
SATELLITE GEARS	COMPOSITE <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
SLIPPER	0.3 mm	NUT 2-PAD SLIPPER CLUTCH PLATES
SOLID AXLE	<input type="checkbox"/>	KIT <input type="checkbox"/> VENTILATED <input checked="" type="checkbox"/>

GEARING		
PINION	21	SPUR GEAR 78
TYPE	GEAR BOX	
FRONT LCG	<input checked="" type="checkbox"/>	REAR LCG <input type="checkbox"/>
HARDNES	KIT <input type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>

FRONT	SHOCKS	REAR
4	SPRINGS	3
cSt 400	OIL	cSt 200
2 HOLES <input type="checkbox"/>	<input type="checkbox"/> 1.6mm <input checked="" type="checkbox"/>	2 HOLES <input type="checkbox"/>
3 HOLES <input checked="" type="checkbox"/>	<input type="checkbox"/> 1.8mm <input type="checkbox"/>	3 HOLES <input type="checkbox"/>
Thickness 2.0mm <input checked="" type="checkbox"/> 2.5mm	KIT <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	Thickness 2.0mm <input checked="" type="checkbox"/> 2.5mm
Precision <input checked="" type="checkbox"/> KIT <input type="checkbox"/>		Precision <input checked="" type="checkbox"/> KIT <input type="checkbox"/>
DOWNSTOP SHIM	0 mm	DOWNSTOP SHIM
LENGTH 22 mm		LENGTH 27 mm
UPSTOP SHIM	0 mm	UPSTOP SHIM
KIT <input type="checkbox"/> ALU <input checked="" type="checkbox"/>		KIT <input type="checkbox"/> ALU <input checked="" type="checkbox"/>
0mm <input type="checkbox"/> -2mm <input checked="" type="checkbox"/> -4mm <input type="checkbox"/>		0mm <input type="checkbox"/> -2mm <input checked="" type="checkbox"/> -4mm <input type="checkbox"/>
	COLLAR	
<input type="checkbox"/> +4mm <input type="checkbox"/> +2mm <input checked="" type="checkbox"/>		<input type="checkbox"/> +4mm <input type="checkbox"/> +2mm <input checked="" type="checkbox"/>
	BALL JOINT	

FRONT	ANTI ROLL BAR	REAR
1.2 mm	THICKNESS	1.4 mm

FRONT	TIRES	REAR
stagger	BRAND	cactus
	COMPOUND	
	INSERTS	
XRAY	WHEELS	HARD

ELECTRONICS		
MOTOR	5.5T	NITRIDE
MOTOR TIMING	30	Nosram 4200
BATTERY		

BODY	Delta 2DL	TOTAL WEIGHT
	<input checked="" type="checkbox"/> LIGHT	/g

COMMENT
---------

FRONT	APPLIED	REAR
<b>CASTER BLOCK</b> MEDIUM - KIT <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU C-HUB <input type="checkbox"/> UP 0 /mm DOWN 2 /mm	<b>LONGER BUSHINGS</b> UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	<b>SHOCK TOWER</b> KIT <input checked="" type="checkbox"/> 4.0mm 3.5mm
<b>STEERING BLOCK</b> MEDIUM - KIT <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	<b>SHIM</b> 2 /mm CAMBER LINK LOCATION	<b>SHIM</b> 2 /mm DRIVE SHAFT <input checked="" type="checkbox"/> KIT 77 /mm SHIM 4 /mm STANDARD ARM DISENGAGED ARM
<b>ARM MOUNT</b> 0° <input type="checkbox"/> KIT 0° <input checked="" type="checkbox"/> ALU -3° <input type="checkbox"/> ALU +3° <input type="checkbox"/> ALU 0° <input type="checkbox"/> BRASS TOTAL 24,5 KICK-UP°	<b>FRONT WING</b> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> KIT <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> SHIM 2 /mm ACKERMANN SHIM 0 /mm CASTER BUSHINGS 0° 25° 5° 0° <input checked="" type="checkbox"/> 25° <input type="checkbox"/> 5° <input type="checkbox"/>	<b>SHIM</b> 2 /mm REAR UPRIGHT HIGH <input type="checkbox"/> LOW <input checked="" type="checkbox"/> #325341 ADJ. DRIVE AXLE
<b>FRONT</b> ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP	<b>WING TYPE</b> Lush CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> WING POSITION UP <input type="checkbox"/> MIDDLE <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	<b>WING TYPE</b> Lush CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> WING POSITION UP <input type="checkbox"/> MIDDLE <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>

FRONT TOE	EXTENSION	BATTERY PLACEMENT	REAR TOE	OFFSET
1	1 DOT <input type="checkbox"/> 2 DOTS <input checked="" type="checkbox"/> 3 DOTS <input type="checkbox"/>	LONG SIDE FRONT <input checked="" type="checkbox"/> LONG SIDE REAR <input type="checkbox"/>	1	3 /slots
OFFSET 0 /slots				
WHEELBASE 2 /mm				
ROLL CENTER KIT <input checked="" type="checkbox"/> ALU <input type="checkbox"/>				
STEERING PLATE KIT <input type="checkbox"/> ALU <input checked="" type="checkbox"/>				
ARMS KIT <input type="checkbox"/> ALU <input checked="" type="checkbox"/>				
SERVO POSITION				
SERVO BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>				
SIDE BRACES KIT <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>				
BATTERY SIZE STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>				
UPPER BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>				
COOLING FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>				

FRONT	REAR
<b>RF</b> 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/> ROLL CENTER SUSPENSION HOLDERS 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/>	<b>RR</b> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> ROLL CENTER SUSPENSION HOLDERS 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/>
Raising the suspension holders with shims.	Raising the suspension holders with shims.

FRONT CAMBER	DIFF HEIGHT	REAR CAMBER
2 °	2	2
GLUING SIDEWALL YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		CUTTING PINS IN <input checked="" type="checkbox"/> OUT <input type="checkbox"/>
FRONT ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>		REAR ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
RISE HEIGHT 13 /mm	RISE HEIGHT 13 /mm	RISE HEIGHT 13 /mm

SERVO WEIGHT	LOWER ECCENTRIC SHOCK BALL	ARM SHIM
STANDARD <input type="checkbox"/> LOW PROFILE <input checked="" type="checkbox"/>	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	0 /mm
ARM MOUNT BALANCE #293085 HUDY Pure Tungsten Weight - 10g.		
BALANCE 10 /g	BALANCE 30 /g	BALANCE 35 /g
BALANCE 10 /g	BALANCE 10 /g	BALANCE 10 /g
ELECTRONICS PLATE NO <input type="checkbox"/> GRAPHITE <input type="checkbox"/> WEIGHT <input checked="" type="checkbox"/>		
CHASSIS SIZE <input type="checkbox"/> SHORT <input checked="" type="checkbox"/> MID-SIZE <input type="checkbox"/> LONG		
THICKNESS <input checked="" type="checkbox"/> 2.5mm KIT <input type="checkbox"/> 2.0mm		