

# SET-UP SHEET

VER.01 ©XRAY

# XRAY X10'22

RACE	Czech nationals RD1	
TRACK	Holešov	
NAME		DATE 2.3

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
	2	1	/sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

CENTER SHOCK ABSORBER	
CENTER SHOCK OIL	750 /cSt
CENTER SHOCK REBOUND	/%
CENTER SHOCK SPRING	3,1 /C

SIDE DAMPING	
OIL	15K /cSt

FRONT	TIRES	REAR
37sh	TIRES TYPE	35sh
53	DIAMETER /mm	
spider-blue	ADDITIVE	
10	ADDITIVE TIMING	15

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
ADDITIVE TREATED AREA			

TRANSMISSION		
BALL DIFF	GEAR DIFF	SOLID AXLE
<input type="checkbox"/> LOOSE <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> TIGHT	OIL /cSt	<input type="checkbox"/>

GEARING	
PINION / T	SPUR GEAR/T 96
FINAL DRIVE RATIO	ROLLOUT

ELECTRONICS	
MOTOR	Reds Vx3 13,5T
SPEEDO	ZX160
SERVO	M12
BATTERIES	

BODY	
TYPE	BPA

COMMENTS
side braces disconnect from rear

FRONT

SHOCK POSITION: 1 2 3 4

SHOCK ABSORBER: SHORT ☒ LONG ☐

SHIMS: 2,5 /mm

SERVO POSITION: FRONT ☒ REAR ☐  
Mount the servo behind or ahead of the servo posts

SHIMS: 2 /mm

SHIMS: 2 /mm

RIDE HEIGHT: 4,2 /mm

FRONT DROOP: 0,8 /mm

MID RIDE HEIGHT: 4,3 /mm

LINKS SHIMS: 0 /mm

REAR DROOP: 0,8 /mm

LINKS SHIMS: 0 /mm

RIDE HEIGHT: 4,6 /mm

FRONT SPRINGS: sil /C

CASTOR: 3,75 /degree

SIDE SPRINGS: black /C

LUBE: 15k /cSt

RIDE HEIGHT WASHER: 0 /mm

CASTER SHIMS: 2,5 /mm

RIDE HEIGHT SHIM: 0 /mm

REAR RIDE HEIGHT ECCENTRIC BUSHINGS: HIGHER 2.5 2.0 1.5 1.0 0.5 0 LOWER 0.5 1.0 1.5 2.0 2.5

FRONT

REAR

CAMBER: 1,5 /degr. LEFT 1,5 /degr. RIGHT

FRONT BRACE: SOFT /NO BRACE ☐ MEDIUM /POST ☐ STIFF /NO POST ☒

POD LINK: ☒ OUTER ☐ INNER

PIVOT MOUNTING POSITION: FORWARD ☐ REARWARD ☒

CHASSIS: GRAPHITE ☒ ALU ☐ ALU FLEX ☐

PIVOT MOUNTING HEIGHT SHIM: 0 /mm

FRONT

REAR

TOE OUT: /degr.

ACKERMANN SHIMS: 0 /mm

BATTERY POSITION: FRONT ☒ REAR ☐

SHIM: 0 /mm

FRONT WIDTH: /mm

ACKERMANN SHIMS: 0 /mm

WHEELBASE POSITION

STEERING LOCK: /degr.

SERVO: STANDARD ☐ MICRO ☒

REAR AXLE: GRAPHITE ☐ STEEL ☒

REAR WIDTH: /mm

REAR TRACK-WIDTH: /mm

WHEELBASE