

SET-UP SHEET

XRAY GTX8'23 SET-UP VER. 01 ©XRAY

XRAY GTX8'23 C-HUB

RACE	ITA Nats Round 2	
TRACK	Giardini Naxos	
NAME	Atilio D'Angelo	DATE 05/05/2024

TEMPERATURE AIR	20	TEMPERATURE TRACK	
LAPS		FINAL POS.	
BEST LAPTIME	15.2 /sec	RACE LENGTH	/min

TRACKS		
CONDITION	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> HIGH

1ST	GEARING	2ND
<input checked="" type="checkbox"/> 13T	<input checked="" type="checkbox"/> 15T	<input checked="" type="checkbox"/> 17T
<input type="checkbox"/> 14T	<input type="checkbox"/> 16T	<input type="checkbox"/> 18T
<input type="checkbox"/> 15T	<input type="checkbox"/> 17T	<input type="checkbox"/> 19T
<input type="checkbox"/> 16T	<input type="checkbox"/> 18T	<input type="checkbox"/> 20T
<input type="checkbox"/> 17T	<input type="checkbox"/> 19T	<input type="checkbox"/> 21T
SPUR GEARS		
<input checked="" type="checkbox"/> 48T	<input type="checkbox"/> 50T	<input checked="" type="checkbox"/> 45T
<input type="checkbox"/> 49T	<input type="checkbox"/> STANDARD	<input type="checkbox"/> 46T
<input type="checkbox"/> 50T	<input type="checkbox"/> GRAPHITE	<input type="checkbox"/> 47T

CLUTCH	
CLUTCH	STANDARD <input checked="" type="checkbox"/>
BM Spring	OTHER
SHOE	SPRINGS TIGHTEN 0.3
	SPRING

FRONT	DIFFERENTIAL	REAR
G	CASE MATERIAL	G
2M	OIL	40k

FRONT	SHOCKS	REAR
800	SPRINGS	1000
STD	OIL	STD
5%	MEMBRANE	5%
<input checked="" type="checkbox"/> 6 HOLES	REBOUND	<input checked="" type="checkbox"/> 6 HOLES
<input type="checkbox"/> 8 HOLES	PISTONS	<input type="checkbox"/> 8 HOLES
<input type="checkbox"/> 10 HOLES	1.1 mm	<input type="checkbox"/> 10 HOLES
	1.2 mm	
	1.3 mm	
	1.4 mm	
	OTHER PISTONS	

FRONT	ANTI-ROLL BAR	REAR
2.3	THICKNESS	2.5

FRONT	TIRES	REAR
TIRES TYPE: SM Y1 & GRP MX2/XM3		

ENGINE	
TYPE	SM5 Senesi
MUFFLER	SM by Nova
MANIFOLD	Genius
PLUG	7
FUEL	Energy GT

BODY TYPE	TOTAL WEIGHT
Fury	3510 /g

COMMENTS
Front: Upper Deck 3mm Rear: double graphite central brace

FRONT	REAR
STEERING BLOCK COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	ANTI-ROLL BAR 1 2 1 2 3 4 LOWER ROLL CENTER ALU <input checked="" type="checkbox"/>
C-HUB COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> X-HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
FRONT ARM SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	UPRIGHT MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>
OFFSET 0 <input type="checkbox"/> +1 <input type="checkbox"/> +2 <input checked="" type="checkbox"/>	OFFSET STANDARD <input type="checkbox"/> +1 <input checked="" type="checkbox"/> +2 <input type="checkbox"/>
CASTER BUSHINGS +2° <input type="checkbox"/> +1° <input type="checkbox"/> 0° <input checked="" type="checkbox"/> -1° <input type="checkbox"/> -2° <input type="checkbox"/>	REAR SHOCK PLATE POSITION IN <input type="checkbox"/> OUT <input type="checkbox"/>
FRONT DROOP 29 MEASURE UNDER WHEEL AXLE #107717 GAUGE	REAR DROOP 28 MEASURE UNDER WHEEL AXLE #107717 HUDY GAUGE

FRONT	REAR
BUMP STEER SHIM /mm STEERING BLOCK 0 STEERING PLATE 3 SHIMS PLACE ALWAYS UNDER	WING HIGH /mm
WHEELBASE SHIM POSITION <input checked="" type="checkbox"/> 0mm <input type="checkbox"/> 2mm SHIMS BEHIND FRONT ARM	GRAPHITE BRACE WITHOUT <input type="checkbox"/> 1-PIECE <input type="checkbox"/> 2-PIECES <input checked="" type="checkbox"/>
FF 1° <input checked="" type="checkbox"/> 0.5° FR 1° <input checked="" type="checkbox"/> 0.5°	REAR DIFFUSOR YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
LOWER ROLL CENTER ECCENTRIC BUSHINGS	RR 1° <input type="checkbox"/> 0.5°

FRONT	REAR
1.5 FRONT TOE OUT	3 REAR TOE IN
TIGHTEN SERVO SAVER MATERIAL TIGHT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> MEDIUM <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> SOFT <input type="checkbox"/>	UPPER PLATE COMPOSITE <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>
WHEELBASE SHIM POSITION <input checked="" type="checkbox"/> 0mm <input type="checkbox"/> 1mm <input type="checkbox"/> 2mm <input type="checkbox"/> 3mm <input type="checkbox"/> 4mm SHIMS IN FRONT OF UPRIGHT	ENGINE MOUNT STANDARD <input checked="" type="checkbox"/> MONOBLOCK <input type="checkbox"/>

FRONT	REAR
2-2.5 FRONT CAMBER	4-4.5 REAR CAMBER
REAR DIFF HEIGHT UP <input type="checkbox"/> DOWN <input type="checkbox"/>	LENGTH mm
RIDE HEIGHT 8 /mm	RIDE HEIGHT 9 /mm