

SET-UP SHEET

SET-UP VER.01 ©XRAY

XRAY XB8E'24 PIVOT BALL

RACE	Latvijas RcOffroad Kauss 1.rd		
TRACK	Kangarnieki		
NAME	Hendrik Lainemäe	DATE	04.05.2024

TEMPERATURE AIR	22	TEMPERATURE TRACK	
-----------------	----	-------------------	--

LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
21	1	28.8 /sec	10 /min

TRACKS			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY
	<input type="checkbox"/> BLUE GROVE	<input checked="" type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS

CONDITION	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WET	<input type="checkbox"/> MUD
-----------	---	--------------------------------	------------------------------	------------------------------

DIFFERENTIAL			
	FRONT	CENTER	REAR
CASE MATERIAL	std	std	std
OIL	15k	7k	3k
CROWN GEAR	13		13

GEARING		
MOTOR PINION	17 /T	46 /T
SPUR GEAR		

FRONT	SHOCKS	REAR
std	TYPE	std
4	SPRINGS	3
cell	MEMBRANE	cell
500 /cSt	OIL	500 /cSt
<input type="checkbox"/> 6 HOLES	PISTONS	<input type="checkbox"/> 6 HOLES
<input checked="" type="checkbox"/> 8 HOLES	1.1 mm	<input checked="" type="checkbox"/> 8 HOLES
<input type="checkbox"/> 10 HOLES	1.2 mm	<input checked="" type="checkbox"/> 8 HOLES
	1.3 mm	<input checked="" type="checkbox"/> 10 HOLES
	1.4 mm	
	OTHER	
VALVE PISTONS		
5+2 HOLES	1.5 mm	5+2 HOLES
6+2 HOLES	1.3 mm	6+2 HOLES
8+2 HOLES	1.4 mm	8+2 HOLES
	1.2 mm	
	1.3 mm	

FRONT	ANTI-ROLL BAR	REAR
2.5 /mm	THICKNESS	2.6 /mm

FRONT	TIRES	REAR
6mik scratch	BRAND	6mik scratch
green	COMPOUND	green
red	INSERTS	red
6mik	WHEELS	6mik

ELECTRONICS	
MOTOR	hw 1900kv
SPEEDO	hw xr8 g3
BATTERY TYPE	nosram 9400mah

<input checked="" type="checkbox"/> STANDARD BATTERY	<input type="checkbox"/> SHORT BATTERY
FRONT	REAR

BODY	OTHER	TOTAL WEIGHT
EASY <input checked="" type="checkbox"/> EASY LIGHT <input type="checkbox"/>		3750 /g

FRONT	REAR
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	UPRIGHT MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
UPPER ARM SHIM/mm 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 1.5 <input type="checkbox"/> 2 <input type="checkbox"/>	ANTI-ROLL BAR 1 <input type="checkbox"/> 2 <input type="checkbox"/>
UPPER ARM WING NONE <input checked="" type="checkbox"/> LEXAN <input type="checkbox"/> CARBON <input type="checkbox"/>	SHOCK TOWERS FRONT ALU <input checked="" type="checkbox"/> CARBON <input checked="" type="checkbox"/> ALU <input type="checkbox"/> REAR ALU <input type="checkbox"/>
PIVOT BALLS UP STEEL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> DOWN STEEL <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	UPPER SHOCK POSITION 1 2 3 4 5 6 7 8
OFFSET 0 <input type="checkbox"/> +1 <input checked="" type="checkbox"/> +2 <input type="checkbox"/>	UPRIGHT ROLL CENTER 1 2 3
PIVOT NUT ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>	REAR ROLL CENTER 1 2 3
FRONT DROOP MEASURE UNDER WHEEL AXLE #107717 GAUGE	UPRIGHT LOWER ROLL CENTER 1 2 3
LOWER ARM SHIM 0 <input checked="" type="checkbox"/> 1mm <input type="checkbox"/> 2mm <input type="checkbox"/>	REAR DROOP MEASURE UNDER WHEEL AXLE #107717 GAUGE

FRONT	REAR
UPPER ROLL CENTER 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	REAR WING <input checked="" type="checkbox"/> COMPOSITE <input type="checkbox"/> LEXAN OTHER <input type="checkbox"/>
CASTER SHIM 0 1.0 1.0 2.0	CUT OUT HOLES FRONT <input type="checkbox"/> MIDDLE <input type="checkbox"/> REAR <input type="checkbox"/>
BUMP STEER SHIM STEERING PLATE 0 /mm STEERING BLOCK 0 /mm	GRAPHITE BRACE WITHOUT <input checked="" type="checkbox"/> 1-PIECE <input type="checkbox"/> 2-PIECES <input type="checkbox"/>
WHEELBASE SHIM POSITION 0mm <input type="checkbox"/> 2mm <input checked="" type="checkbox"/> 4mm <input type="checkbox"/>	WING HOLDER FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>
SHIMS BEHIND FRONT ARM	SHIMS IN FRONT OF REAR ARM
LOWER ROLL CENTER ECCENTRIC BUSHINGS	RR 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>

FRONT	REAR
1 FRONT TOE OUT	3 REAR TOE IN
STEERING PLATE 1 DOTS <input checked="" type="checkbox"/> 2 DOTS <input type="checkbox"/>	CHASSIS KIT <input checked="" type="checkbox"/> LONG +4mm <input type="checkbox"/>
WHEELBASE 0mm <input type="checkbox"/> 1mm <input type="checkbox"/> 2mm <input type="checkbox"/> 3mm <input type="checkbox"/> 4mm <input type="checkbox"/>	SHIMS IN FRONT OF UPRIGHT
SERVO SAVER TIGHT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> SOFT <input type="checkbox"/>	SIDE GUARD SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> CARBON <input type="checkbox"/>
GRAPHITE BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	REAR DRIVE SHAFT CVD <input checked="" type="checkbox"/> UNIVERSAL <input type="checkbox"/> LENGTH /mm
FRONT DRIVE SHAFT CVD <input checked="" type="checkbox"/> UNIVERSAL <input type="checkbox"/> LENGTH /mm	DRIVE SHAFT CVD <input checked="" type="checkbox"/> DOGBONE <input type="checkbox"/>
TOP DECK COMPOSITE <input checked="" type="checkbox"/> CARBON <input type="checkbox"/>	DRIVE SHAFT CVD <input checked="" type="checkbox"/> DOGBONE <input type="checkbox"/>

FRONT	REAR
FRONT CAMBER LENGTH /mm	REAR CAMBER LENGTH /mm
UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	FRONT DIFF HEIGHT 1 2 3 4 5 6 7 8
LOWER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	REAR DIFF HEIGHT 1 2 3 4 5 6 7 8
RIDE HEIGHT 23 /mm	RIDE HEIGHT 25 /mm