

SET-UP SHEET

XRAY XB8'24 SET-UP VER.01 ©XRAY

XRAY XB8'24 PIVOT BALL

| | | | |
|-------|-----------------|------|----------|
| RACE | Silverstate | | |
| TRACK | South Point | | |
| NAME | Paul Ciccarello | DATE | 5 5 2024 |

| | | | |
|-----------------|------|-------------------|------|
| TEMPERATURE AIR | 66 | TEMPERATURE TRACK | |
| LAPS | | FINAL POSITION | |
| BEST LAPTIME | /sec | RACE LENGTH | /min |

| TRACKS | |
|--------|---|
| SIZE | <input type="checkbox"/> OPEN <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT |

| | |
|----------|---|
| TRACTION | <input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH |
|----------|---|

| | |
|---------|---|
| SURFACE | <input type="checkbox"/> SMOOTH <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> BUMPY |
|---------|---|

| | |
|------|---|
| TYPE | <input checked="" type="checkbox"/> HARD PACKED <input checked="" type="checkbox"/> SOFT DIRT <input type="checkbox"/> CLAY |
| | <input type="checkbox"/> BLUE GROVE <input type="checkbox"/> ASTRO TURF <input type="checkbox"/> GRASS |

| | |
|-----------|--|
| CONDITION | <input type="checkbox"/> DRY <input type="checkbox"/> DUSTY <input checked="" type="checkbox"/> WET <input type="checkbox"/> MUD |
|-----------|--|

| DIFFERENTIAL | | | |
|---------------|-------|--------|-------|
| CASE MATERIAL | FRONT | CENTER | REAR |
| OIL | 8 | 7 | 3 |
| CROWN GEAR | 14/46 | | 14/46 |

| GEARING | |
|-------------|--|
| CLUTCH SHOE | 3 <input type="checkbox"/> 4 <input checked="" type="checkbox"/> 2 med alu, 1 carbon |
| SPRINGS | 4 med |
| CLUTCH BELL | 13 /T |
| SPUR GEAR | 48 /T |

| FRONT | SHOCKS | REAR |
|----------|----------|----------|
| kit | TYPE | kit |
| 3 dot | SPRINGS | 358286 |
| Emulsion | MEMBRANE | Emulsion |
| 450 /cSt | OIL | 425 /cSt |

| STANDARD PISTONS | |
|---|---------------------------------|
| <input checked="" type="checkbox"/> 6 HOLES | <input type="checkbox"/> 1.1 mm |
| <input type="checkbox"/> 8 HOLES | <input type="checkbox"/> 1.2 mm |
| <input type="checkbox"/> 10 HOLES | <input type="checkbox"/> 1.3 mm |
| <input type="checkbox"/> 3-1.35/ 3-1.45 | <input type="checkbox"/> 1.4 mm |
| OTHER | 3-1.45/3-1.50 |

| VALVE PISTONS | |
|---------------|--------|
| 5+2 HOLES | 1.5 mm |
| 6+2 HOLES | 1.3 mm |
| 8+2 HOLES | 1.4 mm |
| | 1.2 mm |
| | 1.3 mm |

| FRONT | ANTI-ROLL BAR | REAR |
|---------|---------------|---------|
| 2.2 /mm | THICKNESS | 2.4 /mm |

| FRONT | TIRES | REAR |
|-------|----------|------|
| JC | BRAND | |
| Green | COMPOUND | |
| JC | INSERTS | |
| JC | WHEELS | |

| ENGINE | |
|----------|----------------|
| TYPE | FX 303 |
| MUFFLER | 2169 |
| MANIFOLD | short |
| PLUG | x4 |
| FUEL | Flashpoint 30% |

| BODY | OTHER | TOTAL WEIGHT |
|--|-------|--------------|
| EASY <input type="checkbox"/> EASY LIGHT <input checked="" type="checkbox"/> | | /g |

