

# SET-UP SHEET

XRAY XT8'23 SET-UP VER. 01 ©XRAY

# XRAY XT8'24

RACE	Silverstate		
TRACK	South Point		
NAME	Paul Ciccarello	DATE	5 5 2024
TEMPERATURE AIR	66-68	TEMPERATURE TRACK	
LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
	3	/sec	/min
TRACKS			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input checked="" type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY
TYPE	<input checked="" type="checkbox"/> HARD PACKED	<input checked="" type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY
	<input type="checkbox"/> BLUE GROVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS
CONDITION	<input type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WET
	<input type="checkbox"/> MUD		

DIFFERENTIAL			
FRONT	CENTER	REAR	CASE MATERIAL
CASE MATERIAL			
OIL	10	20	5
CROWN GEAR			
GEARING			
CLUTCH BELL	13	/T	50
SHOE	3 med alu, 1 car		4 med
			SPUR GEAR
			SPRING

FRONT	SHOCKS	REAR
358057-K	TYPE	358057-K
4 dot buggy fr	SPRINGS	tekno yellow
emulsion	MEMBRANE	emulsion
400	OIL	350
/cSt		/cSt
STD. PISTONS		
<input checked="" type="checkbox"/> 6 HOLES	<input type="checkbox"/> 1.1 mm	<input type="checkbox"/> 6 HOLES
<input type="checkbox"/> 8 HOLES	<input type="checkbox"/> 1.2 mm	<input type="checkbox"/> 8 HOLES
<input type="checkbox"/> 10 HOLES	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/> 10 HOLES
<input type="checkbox"/> 5x1.3/1 1.4	OTHER	<input type="checkbox"/> 5x1.3/1 1.5
VALVE PISTONS		
<input type="checkbox"/> 5+2 HOLES	<input type="checkbox"/> 1.5 mm	<input type="checkbox"/> 5+2 HOLES
<input type="checkbox"/> 6+2 HOLES	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/> 6+2 HOLES
<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/> 1.4 mm	<input type="checkbox"/> 8+2 HOLES
	<input type="checkbox"/> 1.2 mm	
	<input type="checkbox"/> 1.3 mm	

FRONT	ANTI-ROLL BAR	REAR
2.2	THICKNESS	2.6
FRONT	TIRES	REAR
JC	BRAND	
Green	COMPOUND	
JC	INSERTS	
JC	WHEELS	

ENGINE	
TYPE	FX 303
MUFFLER	2169
MANIFOLD	s/m
PLUG	x4
FUEL	flashpoint
BODY TYPE	TOTAL WEIGHT
leadfinger	/g
+2 front shock eyelet, 35mm setup blocks	

COMMENT

FRONT	REAR
OFFSET	UPRIGHT
+1 <input type="checkbox"/>	<input type="checkbox"/> ALU
+2 <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
+5 <input checked="" type="checkbox"/>	HARD <input type="checkbox"/>
	GRAPHITE <input type="checkbox"/>
STEERING BLOCK	
COMPOSITE <input type="checkbox"/>	
ALU <input checked="" type="checkbox"/>	
C-HUB	
COMPOSITE <input type="checkbox"/>	
ALU <input checked="" type="checkbox"/>	
CASTER	
16° <input type="checkbox"/>	
18° <input checked="" type="checkbox"/>	
CAMBER LINK LOCATION	
2 1	
LOWER SHOCK POSITION	
3 2 1	
CASTER BUSHINGS	
+2° <input type="checkbox"/>	
+1° <input type="checkbox"/>	
0° <input type="checkbox"/>	
-1° <input type="checkbox"/>	
-2° <input checked="" type="checkbox"/>	
FRONT DROOP	REAR DROOP
27	23
MEASURE UNDER WHEEL AXLE	MEASURE UNDER WHEEL AXLE

FRONT	REAR WING
WHEELBASE SHIM	COMPOSITE <input type="checkbox"/>
0 mm <input type="checkbox"/>	LEXAN <input checked="" type="checkbox"/>
2 mm <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
SHIMS IN FRONT OF FRONT ARM	REDUCE DONFORCE
BUMP STEER SHIMS	FRONT <input checked="" type="checkbox"/>
STEERING PLATE 4 /mm	MIDDLE <input type="checkbox"/>
STEERING BLOCK /mm	REAR <input type="checkbox"/>
REAR BRACES	GRAPHITE BRACE
LONG <input type="checkbox"/>	YES <input checked="" type="checkbox"/>
SHORT <input checked="" type="checkbox"/>	NO <input type="checkbox"/>
WHEELBASE SHIM	YES <input checked="" type="checkbox"/>
0 mm <input type="checkbox"/>	NO <input type="checkbox"/>
2 mm <input checked="" type="checkbox"/>	
SHIMS IN FRONT OF REAR ARM	
FRONT LOWER ROLL CENTER	REAR
ECCENTRIC BUSHINGS	

FRONT	REAR
1 FRONT TOE OUT	3 REAR TOE IN
RADIO CASE	SOFT <input type="checkbox"/>
TIGHTEN	HARD <input checked="" type="checkbox"/>
SERVO SAVER	
MATERIAL	
<input checked="" type="checkbox"/> TIGHT	
<input type="checkbox"/> MEDIUM	
<input type="checkbox"/> SOFT	
WHEELBASE SHIMS	
0 mm <input type="checkbox"/>	
1 mm <input type="checkbox"/>	
2 mm <input type="checkbox"/>	
3 mm <input type="checkbox"/>	
4 mm <input checked="" type="checkbox"/>	
SHIMS IN FRONT OF UPRIGHT	
DRIVE SHAFT	
CVD <input type="checkbox"/>	
UNIVERSAL <input checked="" type="checkbox"/>	
TOP DECK	
COMPOSITE <input checked="" type="checkbox"/>	
GRAPHITE <input type="checkbox"/>	
SIDE GRAPHITE BRACE	
YES <input type="checkbox"/>	
NO <input checked="" type="checkbox"/>	
CHASSIS STIFFENER	
YES <input checked="" type="checkbox"/>	
NO <input type="checkbox"/>	

FRONT	REAR
2 FRONT CAMBER	2 REAR CAMBER
LENGTH	LENGTH
FRONT ARMS	REAR ARMS
MEDIUM <input checked="" type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>
HARD <input type="checkbox"/>	HARD <input type="checkbox"/>
FRONT DIFF HEIGHT	REAR DIFF HEIGHT
34	39
RIDE HEIGHT	RIDE HEIGHT
34	39
MEASURE UNDER WHEEL AXLE	MEASURE UNDER WHEEL AXLE