

# SET-UP SHEET

# XRAY XB4'22

RACE	Club	
TRACK	Adrenaline	
NAME	Ben Decker	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> VERY-HIGH	
SURFACE	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
TYPE	<input checked="" type="checkbox"/> CLAY	<input type="checkbox"/> CARPET
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input checked="" type="checkbox"/> HARD PACKED
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 11k cst	OIL 100k cst	OIL 7k cst

SATELLITE GEARS		
COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>
STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>
40T <input type="checkbox"/> 41T	CROWN GEAR	40T <input type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
	ONE-WAY TIGHTNESS
SLIPPING ADJUSTMENT	LOOSE
	1 CCW TURN (BASIC SETUP)
	FULLY TIGHTEN

GEARING	
PINION	81
CENTER DIFF SPUR	

FRONT	SHOCKS	REAR
	SPRINGS	
cst 650	OIL	cst 550
%	REBOUND	%
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.2mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.3mm	<input type="checkbox"/> 6 HOLES
	<input type="checkbox"/> ø1.4mm	
	<input type="checkbox"/> ø1.6mm	
	<input type="checkbox"/> ø1.7mm	
	CUSTOM PISTONS	
	1.8 mm	1.9 mm

FRONT	ANTI ROLL BAR	REAR
	THICKNESS	

FRONT	TIRES	REAR
Jc	BRAND	Jc
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS	
MOTOR	5.5t
MOTOR TIMING	
	SPEEDO
	BATTERY
BATTERY SIZE	
STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>	

BODY	
TYPE	STANDARD <input checked="" type="checkbox"/> LIGHT

COMMENTS

FRONT	APPLIED	APPLIED	REAR
ALU C-HUB SHIM UP /mm DOWN /mm LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> DRIVE SHAFT CVD <input checked="" type="checkbox"/> ECS Length /mm SHIM mm LOWER SHOCK POSITION #107711 GAUGE DOWNSTOP mm #107701 SUPPORT BLOCKS #107711 GAUGE			REAR UPRIGHT DRIVE SHAFT Length 75 /mm SHIM 2 mm SHIMS 2 /mm HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> #325341 ADJ. DRIVE AXLE 1 2 3 4 1° <input checked="" type="checkbox"/> 0.5° DOWNSTOP mm #107711 GAUGE

FRONT	CASTER	CASTER BLOCK	WING CUTTING LINE	WING SIDE LINE
CASTER 6° <input type="checkbox"/> 7° <input type="checkbox"/> 9° <input checked="" type="checkbox"/> 12° <input type="checkbox"/> OFFSET 0 BUMP STEER SHIM 2 mm	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	1 2 3 4 5 OFFSET 2 /slots UPRIGHT WHEELBASE SHIM 0 /mm IN FRONT OF ARM	HIGHER LOWER WING POSITION UP <input checked="" type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> WING THICKNESS 0.75 <input type="checkbox"/> 1 <input type="checkbox"/> 1.5 TYPE Jc	

FF	FR	ROLL CENTER	RF	RR 2°
<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> ECCENTRIC BUSHINGS UP <input type="checkbox"/> DOWN <input type="checkbox"/>	<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	<input checked="" type="checkbox"/> 2° <input type="checkbox"/> 1° <input type="checkbox"/> 0.5°

FRONT TOE	STEER. PLATE	REAR TOE	GRAPHITE FOR REAR BRACE	REAR BRACE	ARM SHIM
1	HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BUMP STEER SHIM 7 mm SHIM UNDER STEER. PLATE SERVO SAVER SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT <input checked="" type="checkbox"/> MATERIAL STANDARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	IN #36242 PIVOT BALL ECCENTRIC FRONT <input type="checkbox"/> REAR <input type="checkbox"/>	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	2 mm

FRONT CAMBER	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER
2	DOWNSTOP SHIM mm LENGTH mm UPSTOP SHIM mm COLLAR STANDARD <input checked="" type="checkbox"/> -2mm	2 DOWNSTOP SHIM mm LENGTH mm UPSTOP SHIM mm COLLAR STANDARD <input checked="" type="checkbox"/> -2mm	2
	RIDE HEIGHT 19 mm #107720 GAUGE	RIDE HEIGHT 20 mm #107720 GAUGE	

FRONT ARMS	BALANCE	SIDE GUARDS	BALANCE	REAR ARMS
LONG <input type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>		HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>		LONG <input type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>
CHASSIS FLEX SCREW USED <input checked="" type="checkbox"/> SCREW NOT USED <input type="checkbox"/>				