

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	HOBBYWING CUP 2024				
TRACK	SIMARA				
NAME	shin sawada		DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
1	1	16.7 /sec		/	

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	7000 /cSt	
PINION	/T	SPUR GEAR	108 /T	FINAL DRIVE RATIO	5.26

FRONT		SHOCKS		REAR	
2.5,2.8		XRAY SPRINGS		2.8	
375		OIL /cSt		375	
		REBOUND %			
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		FOAM INSERTS		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm
SHOCK LENGTH		8.5 /mm		SHOCK LENGTH	
		8.5 /mm			

1.2		THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2																		
<table border="1"> <tr> <th colspan="2">TIRES</th> </tr> <tr> <td>ADDITIONAL</td> <td></td> </tr> <tr> <td>ADDITIONAL TIMING</td> <td></td> </tr> <tr> <td>WIPE OFF TIME</td> <td></td> </tr> <tr> <td>TIRE WARMERS</td> <td></td> </tr> <tr> <td>Timing:</td> <td>Temp.:</td> </tr> <tr> <td>FRONT LEFT</td> <td>FRONT RIGHT</td> </tr> <tr> <td>REAR LEFT</td> <td>REAR RIGHT</td> </tr> <tr> <td colspan="2">TREATED AREA</td> </tr> </table>						TIRES		ADDITIONAL		ADDITIONAL TIMING		WIPE OFF TIME		TIRE WARMERS		Timing:	Temp.:	FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT	TREATED AREA	
TIRES																							
ADDITIONAL																							
ADDITIONAL TIMING																							
WIPE OFF TIME																							
TIRE WARMERS																							
Timing:	Temp.:																						
FRONT LEFT	FRONT RIGHT																						
REAR LEFT	REAR RIGHT																						
TREATED AREA																							

TOTAL WEIGHT	1320 /g	WEIGHT BALANCE	FRONT %	REAR %
MOTOR	H/W13.5T-B	TIMING		
ESC	G2S	BATTERIES	sunpadow6000	
BODY		WING		

65 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	
Dimension from body post to upper holder		
Dimension from edge to surface		

1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm	
X4'23	
X4'22	
X4'22	
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	
TOP DECK CUTTING	

COMMENTS

FRONT CASTER		FRONT & REAR SUSPENSION		REAR CASTER	
5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° <input type="checkbox"/>	Adjust with eccentric bushings	BUMP STEER	HEIGHT	SHIM	Adjust with eccentric bushings
2 /mm		19 /mm	5 /mm		
2.0 /mm FF	5 /mm	FR 2.0 /mm	<input checked="" type="checkbox"/> SERVO SAVER	TOE GAIN	2.5 /mm RF
<input checked="" type="checkbox"/> RIDE HEIGHT		<input type="checkbox"/> SERVO HORN		2 /mm	5.4 /mm RR
					<input checked="" type="checkbox"/> RIDE HEIGHT
					2.5 /mm

2 /deg.	CAMBER	Left = Right	BODY STOP	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHOCK HOLDERS	SHIM 2.5 /mm	FRONT HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
DRIVE SHAFT: <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP								

2 /deg.	CAMBER	Left = Right	BODY POST	VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>	SHOCK HOLDERS	FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>	SHIM 2.5 /mm	REAR HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
DRIVE SHAFT: <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.6 /mm DOWNSTOP									

1.0	TOE OUT	Left = Right	ACKERMANN	SHIM 0.5 /mm	SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	TOE IN	3.0	Right = Left
DIFF POSITION: <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm UPPER ARM: SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> STEERING BRIDGE: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> STEERING: SHIM /mm PLATE: 8.0mm <input checked="" type="checkbox"/> 7.5mm STD. HUB OFFSET: STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm									

FRONT BOTTOM VIEW		REAR	
STEER. LOCK	2.7 /deg.	T-BRACE	ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
MOTOR MOUNT: FR RE SERVO HOLDER: CHASSIS T-BRACE		CHASSIS: GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm <input type="checkbox"/> REAR ARMS: MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	