

SET-UP SHEET

XRAY XB4'22

RACE	nordic championship	
TRACK	Bukta	
NAME	Søggý	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> VERY-HIGH	
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
TYPE	<input type="checkbox"/> CLAY	<input type="checkbox"/> CARPET
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 10k	OIL 200k	OIL 10k

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T	CROWN GEAR	40T

CENTRAL SLIPPER & ONE-WAY SETTING	
SLIPPING ADJUSTMENT	ONE-WAY TIGHTNESS
<input checked="" type="checkbox"/>	<input type="checkbox"/>
LOOSE	1 CCW TURN (BASIC SETUP)
	FULLY TIGHTEN

GEARING	
PINION 19	CENTER DIFF SPUR

FRONT	SHOCKS	REAR
2 dot	SPRINGS	2 dot
600/550	OIL	400
REBOUND		
<input type="checkbox"/> 2 HOLES <input checked="" type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES	PISTONS <input type="checkbox"/> ø1.2mm <input type="checkbox"/> ø1.3mm <input type="checkbox"/> ø1.4mm <input type="checkbox"/> ø1.6mm <input type="checkbox"/> ø1.7mm CUSTOM PISTONS <input type="checkbox"/> 1.5 mm <input type="checkbox"/> 1.6 mm	<input type="checkbox"/> 2 HOLES <input checked="" type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES

FRONT	ANTI ROLL BAR	REAR
2	THICKNESS	1.8

FRONT	TIRES	REAR
mezzo	BRAND	mezzo
y	COMPOUND	y
schu	INSERTS	schu
	WHEELS	

ELECTRONICS	
MOTOR	SPEEDO
MOTOR TIMING	BATTERY
BATTERY SIZE	
STD. SHORT LOW SHORT	

BODY	
TYPE	STANDARD LIGHT

COMMENTS

FRONT	APPLIED	APPLIED	REAR
ALU C-HUB SHIM UP /mm DOWN /mm LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> DRIVE SHAFT CVD <input checked="" type="checkbox"/> ECS Length /mm SHIM 2 mm LOWER SHOCK POSITION #107711 GAUGE			REAR UPRIGHT DRIVE SHAFT Length /mm SHIM 3 mm SHIMS 2 /mm HARD GRAPHITE ALU #325341 ADJ. DRIVE AXLE 1 2 3 4 1° <input checked="" type="checkbox"/> 0.5° #107711 GAUGE

FRONT	CASTER	CASTER BLOCK	WING CUTTING LINE	WING SIDE LINE
CASTER 6° <input type="checkbox"/> 7° <input type="checkbox"/> 9° <input checked="" type="checkbox"/> 12° <input type="checkbox"/> OFFSET 2 BUMP STEER SHIM 2 mm	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	1 2 3 4 5 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> OFFSET 3 /slots UPRIGHT WHEELBASE SHIM 3 /mm IN FRONT OF ARM	HIGHER LOWER WING POSITION UP <input checked="" type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> WING THICKNESS 0.75 1 1.5 TYPE	

FF	FR	ROLL CENTER	RF	RR
<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> RR 2°

FRONT TOE	STEER. PLATE	REAR TOE	GRAPHITE FOR REAR BRACE	REAR BRACE	ARM SHIM
1	HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> BUMP STEER SHIM 3 mm SHIM UNDER STEER PLATE SERVO SAVER SOFT MEDIUM TIGHT MATERIAL STANDARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>	2.5	YES <input type="checkbox"/> NO <input type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/>	0

FRONT CAMBER	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER
1	DOWNSTOP SHIM 2 mm LENGTH 22 mm UPSTOP SHIM 2 mm	2 DOWNSTOP SHIM 0 mm LENGTH 29 mm UPSTOP SHIM 3 mm	2
RIDE HEIGHT 16 mm			
COLLAR STANDARD <input checked="" type="checkbox"/> -2mm			

FRONT ARMS	BALANCE	SIDE GUARDS	BALANCE	REAR ARMS
LONG <input type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>		HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>		LONG <input type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>
CHASSIS FLEX				
SCREW USED <input checked="" type="checkbox"/> SCREW NOT USED <input type="checkbox"/>				