

SET-UP SHEET

X4F'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'24

RACE	EC Warm UP 25'car		
TRACK	Roeselare		
NAME	Jacques Libar	DATE	30.06.24

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
/	3	3	19.1 /sec	/	/

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 200K /cSt		
PINION / T 38	SPUR GEAR / T 90	FINAL DRIVE RATIO 4.5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /cSt	350
/	REBOUND %	/
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm
SHOCK LENGTH 8.5 /mm		SHOCK LENGTH 8.5 /mm	

1.3 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.4
Ride	TIRES	Ride
TriStar Blue	ADDITIVE	TriStar Blue
15 min	ADDITIVE TIMING	15 min

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1251 /g	WEIGHT BALANCE	FRONT 67 % REAR 33 %
--------------	----------------	----------------	------------------------------------

MOTOR	21.5	TIMING	
ESC	/	BATTERIES	Nosram 4200
BODY	YRS	WING	std

		BODY POSITION Dimension from body post to window bottom line / /mm
		WING SIDE PLATE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> Dimension from body post to upper holder / /mm
		Dimension from edge to surface / /mm

	TOP DECK CUTTING <input checked="" type="checkbox"/>
--	---

Body fitted to EFRA rules
Damper screws all in

FRONT & REAR SUSPENSION	
FRONT CASTER <input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 3 /mm HEIGHT 19 /mm SHIM 4 /mm	TOE GAIN 5 /mm
2.0 /mm FF 5.0 /mm FR 2.0 /mm RIDE HEIGHT <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN	2.0 /mm RF 5.2 /mm RR 2.0 /mm RIDE HEIGHT <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN

2.0 /deg. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> / /mm	FRONT SUSPENSION FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> FRONT SHOCK POSITION 1 2 BULKHEAD SHIMS YES <input type="checkbox"/> 3mm <input type="checkbox"/> NO DRIVE SHAFT 58mm 59mm BEARING BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP	FRONT HUB HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> SHIM 0.5 /mm
---	--	---	---

2.0 /deg. CAMBER Left = Right	REAR SUSPENSION REAR SHOCK POSITION 1 2 SHIM 1.5 /mm	REAR HUB HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> SHIM 4.0 /mm DOWNSTOP
---	--	---

0.5 TOE OUT Left = Right DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> composite	FRONT TOP VIEW STEERING ARM & BRIDGE DUAL STD. <input type="checkbox"/> BRIDGE <input type="checkbox"/> <input checked="" type="checkbox"/> SINGLE SHIMS /mm Battery weight plate. ACKERMANN SHIM 1.0 /mm STEERING PLATE 8.0mm STD. <input type="checkbox"/> 7.5mm <input type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	3.0 TOE IN Left = Right UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> composite STEERING PLATE 8.0mm STD. <input type="checkbox"/> 7.5mm <input type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm
---	---	--

WEIGHT LEFT & RIGHT #309825 YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	FRONT BOTTOM VIEW STEER. LOCK 26 /deg. STEER. SHIM SIZE / /mm FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BUMPER WEIGHT #309824 YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR BOTTOM VIEW T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> CHASSIS T-BRACE REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> CHASSIS GRAPHITE <input checked="" type="checkbox"/>
--	--	--

COMMENTS