

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	ETS rd. 3				
TRACK	Luxembourg				
NAME	Valent Gerg		DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
	6	/sec	/		

TRACK					
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT			
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input checked="" type="checkbox"/> FAST		
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH		

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	7000	/cSt
PINION	45	SPUR GEAR	90	FINAL DRIVE RATIO	3,8

FRONT		SHOCKS		REAR	
2.5-2.8		XRAY SPRINGS		2.7	
350		OIL /cSt		350	
--		REBOUND %		--	
<input type="checkbox"/> YES <input type="checkbox"/> NO		FOAM INSERTS		<input type="checkbox"/> YES <input type="checkbox"/> NO	
<input checked="" type="checkbox"/> 4 HOLES	1.1mm	1.1mm		<input checked="" type="checkbox"/> 4 HOLES	1.1mm
<input type="checkbox"/> PSS	1.2mm	1.2mm		<input type="checkbox"/> PSS	1.2mm
SHOCK LENGTH		8,5	/mm	8,5	/mm
1,1		THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1,2

Matrix 36R	TIRES	Matrix 36R
MR 33	ADDITIVE	MR 33
25 min.	ADDITIVE TIMING	25 min.
--	WIPE OFF TIME	--
Timing: 25	Temp.: 70	Timing: 25
Temp.: 70		Temp.: 70
FRONT LEFT	FRONT RIGHT	REAR LEFT
REAR RIGHT		
TREATED AREA		

TOTAL WEIGHT	1325	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	------	----------------	------------	-----------

MOTOR	ETS 17,5	TIMING	
ESC	ETS Orca	BATTERIES	LRP 8100
BODY	Wolverine 0,4	WING	Std.

66	/mm	Dimension from body post to window bottom line	BODY POSITION
6+2		Dimension from body post to upper holder	WING SIDE PLATE
			YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
52	/mm	Dimension from edge to surface	

X4'23	1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'22	2.0mm	<input type="checkbox"/> 1.6mm	
X4'22	2.0mm	<input type="checkbox"/> 1.6mm	
	NONE	<input type="checkbox"/> BEARING	

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
1.5 /mm	4 /mm
HEIGHT	SHIM
19 /mm	4 /mm
TOE GAIN	TOE IN
1.5 /mm	2.5 /mm
SHIM	SHIM
3 /mm	3 /mm
FRIDE HEIGHT	FRIDE HEIGHT
5 /mm	5.2 /mm
RR 3.5 /mm	

FRONT	
2	/deg. CAMBER
Left = Right	
BODY STOP	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
SHOCK HOLDERS	SHIM 2 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	58mm 59mm BEARING BLADE
SHIM	1.5 /mm
SHIM	3 /mm
FRONT HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM	0.5 /mm
DOWNSTOP	5.4 /mm

REAR	
2	/deg. CAMBER
Left = Right	
BODY POST	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS	FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	52mm 54mm BEARING BLADE
SHIM	1.5 /mm
SHIM	3 /mm
REAR HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM	1 /mm
DOWNSTOP	4.6 /mm

FRONT TOP VIEW		REAR	
1	TOE OUT	2.5	TOE IN
Left = Right		Left = Right	
ACKERMANN	SHIM /mm	SHORT LiPo BRASS WEIGHT	YES <input type="checkbox"/> NO <input type="checkbox"/>
BRASS WEIGHT FOR MOTOR MOUNT	40g	BRASS WEIGHT FOR MOTOR MOUNT	40g
DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM	SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> X.soft <input checked="" type="checkbox"/>	UPPER ARM	SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> X.soft <input checked="" type="checkbox"/>
STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING	SHIM /mm
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	HUB OFFSET	STD. <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW		REAR	
STEER. LOCK	27° /deg.	T-BRACE	ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER	FR RE	CHASSIS T-BRACE	
FRONT ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
CHASSIS	GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm <input type="checkbox"/>		