

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	2024 ROAR PAVED NATS VTA				
TRACK	N-CONTROL				
NAME	BRANDAN HICKSON	DATE	9/22/14		
QUAL POSITION	Tq	FINAL POSITION	P1	BEST LAPTIME	/sec
LAPS	/				

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	3000 /cst	<input checked="" type="checkbox"/> FRONT SOLID AXLE
PINION	50 /T	GEAR DIFF OIL
SPUR GEAR	92 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.7	XRAY SPRINGS	2.5
375	OIL /Cst	375
REBOUND %		
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	SHOCK LENGTH
1.2	THICKNESS/mm	1.2

GRAVITY VTA	TIRES
NONE	ADDITIVE
10min	ADDITIVE TIMING
	WIPE OFF TIME
Timing: 10min	Temp.: TIRE WARMERS
FRONT LEFT	FRONT RIGHT
REAR LEFT	REAR RIGHT
TREATED AREA	

TOTAL WEIGHT	1430 /g	WEIGHT BALANCE	FRONT 52 % REAR 48 %
MOTOR	Orca 25.5	TIMING	48
ESC	Orca m2	BATTERIES	PCR 6000
BODY		WING	

	BODY POSITION
	WING SIDE PLATE
	YES <input type="checkbox"/> NO <input type="checkbox"/>
	1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm
	2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/>
	NONE <input type="checkbox"/> BEARING <input type="checkbox"/>

Only sauce rear tire heat all. Front tire edge glue. Clean with GS SAG. Front top deck added brace, 77g Front of mm

FRONT & REAR	SUSPENSION

FRONT	SHOCK HOLDERS	SHIM	SHOCK FLEX	DRIVE SHAFT	FRONT HUB
1 /deg. CAMBER	SHIM 2 /mm	3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	58mm 59mm	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
2.5 /deg. CAMBER	SHIM 2 /mm	2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	SHIM 1.5 /mm
2.25 /deg. CAMBER	SHIM 2 /mm	2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	SHIM .5 /mm

FRONT	SHOCK HOLDERS	SHIM	SHOCK FLEX	DRIVE SHAFT	FRONT HUB
1 /deg. CAMBER	SHIM 2 /mm	3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	52mm 54mm	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
2.25 /deg. CAMBER	SHIM 2 /mm	2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	SHIM .5 /mm
2.25 /deg. CAMBER	SHIM 2 /mm	2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	SHIM .5 /mm

FRONT	TOP VIEW	REAR

FRONT	BOTTOM VIEW	REAR