

SET-UP SHEET

X4F'25 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'25

RACE	MRC Longwy Winterseries Rd.1		
TRACK	Longwy		
NAME	Jacques Libar	DATE	20.10.24

TRACK TEMP.	QUAL. POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
/	1	1	13.5 /sec	/	/

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 150K /cSt		
PINION / T 38	SPUR GEAR / T 100	FINAL DRIVE RATIO 5.0

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /Cst	350
/	REBOUND %	/

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm		SHOCK LENGTH 8.5 /mm	

1.4 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.6
-------------------------	---------------	-------------------------

ETS Ride		TIRES
MR 33 V4		
15-20 min		
5		
Timing:	Temp.:	ADDITIVE
		ADDITIVE TIMING
		WIPE OFF TIME
		TIRE WARMERS
Timing:	Temp.:	

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1253 /g	WEIGHT BALANCE	FRONT 66 %	REAR 34 %
--------------	----------------	----------------	-------------------	------------------

MOTOR	HW ETS 17.5	TIMING		RPM LIMIT
ESC	HW limiter	BATTERIES	Nosram 4200	
BODY	YRS	WING	std	

55 /mm	Dimension from body post to window bottom line	BODY POSITION
low /mm	Dimension from body post to upper holder	WING SIDE PLATE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
low /mm	Dimension from edge to surface	

<input checked="" type="checkbox"/>	TOP DECK CUTTING
<input type="checkbox"/>	TOP DECK FLEX

COMMENTS	
----------	--

FRONT & REAR SUSPENSION	
FRONT CASTER <input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input checked="" type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 2 /mm HEIGHT 19 /mm SHIM 4 /mm	TOE GAIN 4 /mm
2 /mm FF 5.2 /mm FR 2 /mm RIDE HEIGHT <input checked="" type="checkbox"/> SERVO SAVER <input checked="" type="checkbox"/> SERVO HORN	2.0 /mm RF 5.6 /mm RR 2.0 /mm RIDE HEIGHT <input checked="" type="checkbox"/>

2 /degr. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm	FRONT SUSPENSION SHOCK HOLDERS SHIM 4 /mm	FF /mm 2 FR /mm 2 SHIMS 3 /mm	FRONT HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
DRIVE SHAFT <input type="checkbox"/> 58mm <input checked="" type="checkbox"/> 59mm <input checked="" type="checkbox"/> BEARING <input checked="" type="checkbox"/> BLADE		SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIM 0.5 /mm	SHIM 0.5 /mm
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP				

2 /degr. CAMBER Left = Right	REAR SUSPENSION SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/> SHIM 4 /mm	RF /mm 2 RR /mm 2 SHIMS 3 /mm	REAR HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		SHIM 1 /mm	SHIM 1 /mm
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.2 /mm DOWNSTOP			

FRONT TOP VIEW		REAR	
0.5 TOE OUT Left = Right	DIFF POSITION UP <input checked="" type="checkbox"/> +1mm <input type="checkbox"/> DOWN <input type="checkbox"/> STD. <input checked="" type="checkbox"/>	1 TOE IN Left = Right	ARS LINKS SHIMS kit /mm
UPPER ARM COMPOSITE <input type="checkbox"/> EXTRA SOFT <input checked="" type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/>	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	UPPER ARM COMPOSITE <input type="checkbox"/> EXTRA SOFT <input checked="" type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/>	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW		REAR	
WEIGHT LEFT & RIGHT #309826 YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	STEER. LOCK 26 /degr.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	CHASSIS T-BRACE
BUMPER WEIGHT YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	MOTOR MOUNT	FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>