

# SET-UP SHEET

X4'25 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'25

RACE	US indoor champs 2024				
TRACK	Independence				
NAME	Adam Izsay		DATE	28.11-1.12	
QUAL POSITION	3	FINAL POSITION	2	BEST LAPTIME	11.7 /sec
LAPS	/				

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
	90	

FRONT	SHOCKS	REAR
2.6	XRAY SPRINGS	2.6
350	OIL /Cst	350
0	REBOUND %	0

<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES	1.1mm	1.1mm
<input checked="" type="checkbox"/> PSS	1.2mm	1.2mm

SHOCK LENGTH	7	SHOCK LENGTH	7
--------------	---	--------------	---

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Gravity	SXT 3.0
10	ADDITIVE
2	ADDITIVE TIMING
Timing:	Temp.:

SIDE WALL GLUE	DIA. No
FRONT TIRES	ADDITIVE AREA
	Full

TOTAL WEIGHT	1322	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	------	----------------	------------	-----------

MOTOR	HW G4R 21.5	TIMING	
ESC	HW G3X	BATTERIES	Nosram 5100
BODY	Wolverine 0.4	WING	Superrad

64	Dimension from body post to window bottom line	BODY POSITION
51	Dimension from edge to surface	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>

X4'23	GF	1.6mm	<input checked="" type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm	<input checked="" type="checkbox"/>	GF
	SCREWS			SHIMS				
Rear used in front								
X4'22		2.0mm	<input type="checkbox"/>	1.6mm	<input type="checkbox"/>			
	NONE			BEARING				

COMMENTS

FRONT CASTER	Upper links CASTER	FRONT & REAR SUSPENSION	REAR CASTER	Upper links CASTER
Adjust with eccentric bushings			Adjust with eccentric bushings	
5° 4° 3°			0.5° 1.5° 2.5° 3.5° 4.5° 5.5°	
BUMP STEER	HEIGHT	SHIM		
1.5 /mm	19 /mm	3.5 /mm		
2 /mm	5 /mm	FR 2 /mm	TOE GAIN	2.5 /mm
RIDE HEIGHT		<input checked="" type="checkbox"/> SERVO SAVER	1 /mm	RF 5.2 /mm
		<input checked="" type="checkbox"/> SERVO HORN		RR 2.5 /mm

FRONT
2 /deg. CAMBER
Left = Right
BODY STOP
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
SHOCK HOLDERS
SHIM 6 /mm
SHOCK TOWER SCREW
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT
58mm 59mm BEARING BLADE
FF 1.5 /mm
FR 1.5 /mm
SHIM 2 /mm
FRONT HUB
MEDIUM <input type="checkbox"/>
HARD <input type="checkbox"/>
GRAPHITE <input checked="" type="checkbox"/>
ALU <input type="checkbox"/>
SHIM 0.5 /mm
DOWNSTOP
6 /mm
Set with shocks <input type="checkbox"/> Set without shocks <input checked="" type="checkbox"/>

REAR
2 /deg. CAMBER
Left = Right
BODY POST
VERTICAL <input type="checkbox"/>
HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS
FIXED <input type="checkbox"/> ACTIVE <input checked="" type="checkbox"/>
SHIM 6 /mm
SHOCK TOWER SCREW
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT
52mm 54mm BEARING BLADE
RF 1.5 /mm
RR 1.5 /mm
SHIM 2 /mm
REAR HUB
MEDIUM <input type="checkbox"/>
HARD <input type="checkbox"/>
GRAPHITE <input checked="" type="checkbox"/>
ALU <input type="checkbox"/>
SHIM 1 /mm
DOWNSTOP
4 /mm
Set with shocks <input type="checkbox"/> Set without shocks <input checked="" type="checkbox"/>

FRONT TOP VIEW	REAR
1 TOE OUT	2.5 TOE IN
Left = Right	Left = Right
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM 0.5 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION	BRASS WEIGHT FOR MOTOR MOUNT
<input checked="" type="checkbox"/> UP	40g
<input type="checkbox"/> DOWN	12
<input type="checkbox"/> +1mm	40g
FRONT UPPER ARM	SHIM
LINKS	/mm
C <input type="checkbox"/>	
X <input checked="" type="checkbox"/>	
S <input type="checkbox"/>	
M <input type="checkbox"/>	
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM/mm
HUB OFFSET	PLATE
<input checked="" type="checkbox"/>	8.0mm 7.5mm STD.
SHIM/mm	
REAR UPPER ARM	LINKS
C <input type="checkbox"/>	
X <input checked="" type="checkbox"/>	
S <input type="checkbox"/>	
M <input type="checkbox"/>	
HUB OFFSET	SHIM/mm
<input checked="" type="checkbox"/>	

FRONT BOTTOM VIEW	REAR
BUMPER	T-BRACE
3D - KIT <input checked="" type="checkbox"/>	ALU BRASS
FOAM <input type="checkbox"/>	
STEER. LOCK	
26 /deg.	
MOTOR MOUNT	
SERVO HOLDER	
CHASSIS	
GRAPHITE <input type="checkbox"/>	
ALU <input checked="" type="checkbox"/>	
ALU 1.5mm	
FRONT ARMS	REAR ARMS
MEDIUM <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
HARD <input checked="" type="checkbox"/>	HARD <input checked="" type="checkbox"/>
GRAPHITE <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>