

SET-UP SHEET

XRAY X1'20

RACE				
TRACK	Basic Setting			
NAME	Jan Ratheisky	DATE	2020 ;)	
TEMPERATURE AIR	X	TEMPERATURE TRACK	X	
QUAL POSITION	X	FINAL POSITION	X	
BEST LAP TIME	X	LAPS	X	
TIME			X	

TRACK				
TRACK SURFACE	<input type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT		
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST	
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH	

CENTER SHOCK ABSORBER		
SPRING	OIL /cSt	REBOUND %
2.3-2.5	1000	
PISTON	PISTON HOLES DIAMETER	FOAM INSERT
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.1mm	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> ø1.2mm	
	<input type="checkbox"/> ø1.3mm	

ANTI-ROLL BAR	
THICKNESS/mm	

SIDE DAMPING	
<input checked="" type="checkbox"/> SIDE TUBE	OIL 30000 /cSt
<input type="checkbox"/> SIDE SHOCK	OIL /cSt

FRONT	TIRES	REAR
X	TIRES	X
X	ADDITIVE	X
20	ADDITIVE TIMING	20
FRONT LEFT	ADDITIVE TREATED AREA	REAR LEFT
FRONT RIGHT		REAR RIGHT

TRANSMISSION		
BALL DIFF	SOLID AXLE	GEAR DIFF
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
LOOSE		OIL 3000 /cSt

GEARING		
PINION /T	SPUR GEAR /T	FINAL DRIVE RATIO

ELECTRONICS	
MOTOR	
SPEEDO	
BATTERIES	

BODY	

FRONT		REAR	
BUMP STEER	SHOCK PYTE	SHIM	SHIM
SHIM /mm	SHORT	nut/mm	nut/mm
SERVO ARM	LONG		
DROOP 0.8	4.0	FRONT RIDE HEIGHT	MID RIDE HEIGHT 4.2
		DROOP 1.4	REAR RIDE HEIGHT

WHEELBASE ADJUSTMENT	
LONG (+4mm)	SHORT (-4mm)
STANDARD (0mm)	

SHIM		ALU MOUNT		UPPER ARM		SIDE SPRING		RIDE HEIGHT		WING	
SHIM 0.5-1 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIM 1 /mm	0mm <input checked="" type="checkbox"/> CENTER	+1mm <input type="checkbox"/> REARWARD	-1mm <input type="checkbox"/> FRONTWARD	SILVER C=0.6	GOLD C=0.9	BLACK C=1.2	SILVER C=1.5	GOLD C=1.8	SHIM 1 /mm
SHIM 2.5 /mm											
SHIM 0.5 /mm											
LUBE 10000 /cSt											
SHIM 0.5 /mm		SPRING 1.5	LOWER ARM SHIM 1 /mm								

ARM MOUNT PLATE		CAMBER	
STANDARD <input checked="" type="checkbox"/>	WIDE <input type="checkbox"/>	1.0° <input type="checkbox"/>	1.5° <input checked="" type="checkbox"/>
		2.0° <input type="checkbox"/>	2.5° <input type="checkbox"/>

CASTER		LOWER ARMS	
3° <input type="checkbox"/>	6° <input type="checkbox"/>	STANDARD GRAPHITE <input checked="" type="checkbox"/>	SOFT GRAPHITE ARMS <input type="checkbox"/>
9° <input checked="" type="checkbox"/>	12° <input type="checkbox"/>		

CHASSIS		BATTERY POSITION		REAR WING	
GRAPHITE 2.5mm (KIT) <input checked="" type="checkbox"/>	HARD GRAPHITE <input type="checkbox"/>	INLINE <input type="checkbox"/>	CROSS CHASSIS <input type="checkbox"/>	STANDARD <input type="checkbox"/>	OTHER: <input type="checkbox"/>
ALU <input type="checkbox"/>	ALU FLEX <input type="checkbox"/>				

TOE		POD LINK		REAR AXLE	
OUT 2 /deg.		Left=Right	STEEL <input type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>	ADJUSTABLE <input checked="" type="checkbox"/>

GRAPHITE BRACE		SHIM USED		STEERING ANGLE		TOP DECK		TOP DECK FLEX		REAR WIDTH		REAR WING POSITION	
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		26 /°	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SOFT <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/>	STIFF <input type="checkbox"/>	SHIM 2.5 /mm	1 2 3 4 5 6			

COMMENTS