

SET-UP SHEET

XRAY XB2'20

RACE	EOS Round 1 Daun		
TRACK	EOS Daun		
NAME	Martin Bayer	DATE	2020-02-02

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	6th	FINAL POSITION	5th

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH		
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

TRANSMISSION			
DIFFERENTIAL	BALL DIFF <input type="checkbox"/>	<input checked="" type="checkbox"/> GEAR DIFF	OIL 8k <input type="checkbox"/> cSt
SATELLITE GEARS	COMPOSITE <input type="checkbox"/>	<input checked="" type="checkbox"/> STEEL	GEARS 2 <input checked="" type="checkbox"/> 4
SLIPPER	2 PAD <input type="checkbox"/>	<input checked="" type="checkbox"/> 3 PAD	<input type="checkbox"/> mm

GEARING			
PINION	23	SPUR GEAR	78

GEAR BOX	
FRONT LCG	<input checked="" type="checkbox"/> FRONT LCG <input type="checkbox"/> REAR LCG

FRONT	SHOCKS	REAR
2 42mm	SPRINGS	500
cSt 500	OIL	cSt
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input checked="" type="checkbox"/> ø1.6mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 6 HOLES
OTHER: mm mm		
SHOCK BODY		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
SHOCK SHAFT		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
DOWNSTOP SHIM		
INSERT UNDER PISTON		
LENGTH 24 mm		LENGTH 31 mm
UPSTOP SHIM		UPSTOP SHIM
INSERT ABOVE COLLAR		INSERT ABOVE COLLAR
OTHER: mm	<input checked="" type="checkbox"/> KIT BALL JOINT	OTHER: mm

FRONT	SHOCK TOWER	REAR
ALU <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	ALU <input type="checkbox"/>

FRONT	ANTI ROLL BAR	REAR
0,8 mm	THICKNESS	1,0 mm

FRONT	TIRES	REAR
EOS	BRAND	EOS
EOS	COMPOUND	EOS
EOS	INSERTS	EOS
EOS	WHEELS	

ELECTRONICS			
MOTOR	Hobbywing 6	HW XR10 PR	SPEEDO
MOTOR TIMING	30	Sunpadow	BATTERY

BODY	
ALPHA2 <input type="checkbox"/>	<input checked="" type="checkbox"/> BETA2
OTHER: <input checked="" type="checkbox"/> LIGHT	

COMMENT

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>	LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	REAR UPRIGHT SHIM <input type="checkbox"/> /mm SHIM 4 /mm DRIVE SHAFT Length 75 /mm SHIM 2 /mm ADJUSTABLE DRIVE AXLE 0.5° <input type="checkbox"/> 1° <input type="checkbox"/>
CASTER BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	CAMBER LINK LOCATION SHIM /mm FLAT ARM LSM ARM	XB2D SUSP. ARM XB4 SUSP. ARM

FRONT	WING POSITION	WING CUTTING LINE / SIDE LINE	WING TYPE
CASTER BUSHINGS 0° <input type="checkbox"/> 2.5° <input checked="" type="checkbox"/> 5° <input type="checkbox"/>	UPPER DECK <input checked="" type="checkbox"/> WING POSITION YES <input type="checkbox"/> NO <input type="checkbox"/> SHOCK TOWER	1 2 3 4 5 SHOCK POSITION FRONT <input type="checkbox"/> REAR <input type="checkbox"/>	tec CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
KICK-UP KIT 26° <input type="checkbox"/> 23 <input checked="" type="checkbox"/>	BUMP STEER SHIM /mm STEERING BUMP STEER	WING POSITION UP <input type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/>	

FRONT TOE	OUT	EXTENSION	REAR TOE	IN
1		0 SLOTS <input type="checkbox"/> 1 SLOT <input checked="" type="checkbox"/> 2 SLOTS <input type="checkbox"/>	2	
OFFSET -0,75/slots		BATTERY PLACEMENT LONG SIDE FRONT <input checked="" type="checkbox"/> LONG SIDE REAR <input type="checkbox"/>	OFFSET 6 /slots	
WHEELBASE SHIM 2 /mm		BATTERY SIZE STD. SHORT <input type="checkbox"/> LOW SHORT <input type="checkbox"/>	WHEELBASE SHIM 1 /mm	
ROLL CENTER MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> ALU <input checked="" type="checkbox"/>		UPPER BRACE YES <input type="checkbox"/> NO <input type="checkbox"/>	ROLL CENTER COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	
UPPER DECK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/>		GUARD BRACE FLEX		

FRONT	SHIMS	REAR ROLL CENTER HOLDERS
SHIMS 2 /mm	5 /mm	ECCENTRIC BUSHINGS
ACKERMANN LEFT = RIGHT		RF 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/>
STEERING ARMS COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	BUMP STEER SHIM 1 /mm	RR 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/>
STEERING PLATE COMPOSITE <input type="checkbox"/> ALU <input type="checkbox"/>		

FRONT CAMBER	DIFF HEIGHT	REAR CAMBER
	2	
FRONT ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	RIDE HEIGHT 14 /mm	REAR ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
	RIDE HEIGHT 14 /mm	

ARM MOUNT	ECCENTRIC SHOCK BALL	ARM SHIM
COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	/mm
CHASSIS BRACE MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	SERVO POSITION BALANCE 17 g	CHASSIS ALU 2.5mm <input checked="" type="checkbox"/>
SERVO WEIGHT STANDARD <input checked="" type="checkbox"/> LOW PROFILE <input type="checkbox"/>	BALANCE 45 g	CHASSIS FLEX SCREW USED <input type="checkbox"/> SCREW NOT USED <input checked="" type="checkbox"/>