

SET-UP SHEET

XRAY XB2'20

RACE	MRCF GP	
TRACK	MRCF	
NAME		DATE 2020-09-13

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	2	FINAL POSITION	2

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION			
SURFACE	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input checked="" type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

TRANSMISSION			
DIFFERENTIAL	BALL DIFF <input type="checkbox"/>	<input checked="" type="checkbox"/> GEAR DIFF	OIL 5000 cst
SATELLITE GEARS	COMPOSITE <input type="checkbox"/>	<input checked="" type="checkbox"/> STEEL	GEARS 2 <input type="checkbox"/> 4 <input checked="" type="checkbox"/>
SLIPPER	2 PAD <input type="checkbox"/>	<input checked="" type="checkbox"/> 3 PAD	mm

GEARING			
PINION	23	SPUR GEAR	78

GEAR BOX	
FRONT LCG	<input checked="" type="checkbox"/> FRONT LCG <input type="checkbox"/> REAR LCG

FRONT	SHOCKS	REAR
3 dots	SPRINGS	450
cst 550	OIL	cst
<input checked="" type="checkbox"/> 2 HOLES	<input checked="" type="checkbox"/> ø1.6mm	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	OTHER: mm mm	<input type="checkbox"/> 6 HOLES
SHOCK BODY		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
SHOCK SHAFT		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
DOWNSTOP SHIM		
INSERT UNDER PISTON mm mm		
LENGTH mm mm		
UPSTOP SHIM		
INSERT ABOVE COLLAR mm mm		
OTHER: KIT BALL JOINT KIT 1 OTHER		

FRONT	SHOCK TOWER	REAR
ALU <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	ALU <input type="checkbox"/>

FRONT	ANTI ROLL BAR	REAR
1 mm	THICKNESS	1 mm

FRONT	TIRES	REAR
chum Stagg	BRAND	chum cactu
Yellow	COMPOUND	Yellow
	INSERTS	Medium
	WHEELS	

ELECTRONICS			
MOTOR	Orca 6.5t	Orca OE1	SPEEDO
MOTOR TIMING	30	Orca 4200 LC	BATTERY

BODY	
ALPHA2 <input type="checkbox"/>	<input checked="" type="checkbox"/> BETA2 OTHER: <input type="checkbox"/> LIGHT

COMMENT

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	REAR UPRIGHT SHIM 2 /mm SHIM 4 /mm DRIVE SHAFT Length 75 /mm SHIM 4 /mm ADJUSTABLE DRIVE AXLE 0.5° 1° XB2D SUSP. ARM XB4 SUSP. ARM
CASTER BLOCK MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	CAMBER LINK LOCATION SHIM /mm FLAT ARM LSM ARM	

FRONT	WING POSITION	WING CUTTING LINE / SIDE LINE	WING TYPE
CASTER BUSHINGS 0° <input type="checkbox"/> 2.5° <input checked="" type="checkbox"/> 5° <input type="checkbox"/>	YES <input type="checkbox"/> NO <input type="checkbox"/>	1 2 3 4 5 1 2 3 4 5	TEC CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
KICK-UP KIT 26° <input checked="" type="checkbox"/>	SHOCK TOWER BUMP STEER SHIM /mm	SHOCK POSITION FRONT <input type="checkbox"/> REAR <input type="checkbox"/>	WING POSITION UP <input type="checkbox"/> MIDDLE <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>

FRONT	BATTERY PLACEMENT	REAR
FRONT TOE OUT OFFSET /slots WHEELBASE SHIM 2 /mm ROLL CENTER MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	EXTENSION 0 SLOTS <input type="checkbox"/> 1 SLOT <input checked="" type="checkbox"/> 2 SLOTS <input type="checkbox"/> LONG SIDE FRONT LONG SIDE REAR BATTERY SIZE STD. SHORT <input type="checkbox"/> LOW SHORT <input type="checkbox"/> UPPER BRACE YES <input type="checkbox"/> NO <input type="checkbox"/>	REAR TOE IN OFFSET 5 /slots WHEELBASE SHIM 1 /mm ROLL CENTER COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>
UPPER DECK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/>	GUARD BRACE FLEX 1 2 3 4 5 6 7 8	

FRONT	SHIMS	REAR ROLL CENTER HOLDERS
SHIMS /mm ACKERMANN LEFT = RIGHT	SHIMS 2 /mm BUMP STEER SHIM 1 /mm LEFT = RIGHT	ECCENTRIC BUSHINGS RF 0.5° <input type="checkbox"/> 1° <input type="checkbox"/> RR 0.5° <input type="checkbox"/> 1° <input type="checkbox"/>
STEERING ARMS COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	STEERING PLATE COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	

FRONT	DIFF HEIGHT	REAR
FRONT CAMBER 2° FRONT ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	1 2 3 4 5 6 7 8 1 2 3 4 5 6 7 8 RIDE HEIGHT 15 /mm #107721 GAUGE	REAR CAMBER REAR ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>

FRONT	ECCENTRIC SHOCK BALL	REAR
ARM MOUNT COMPOSITE <input type="checkbox"/> ALU <input type="checkbox"/> BRASS <input checked="" type="checkbox"/>	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/> SERVO POSITION 1 2 3 4 BALANCE g BALANCE 35 g	ARM SHIM 2 /mm CHASSIS ALU 2.5mm <input checked="" type="checkbox"/>
CHASSIS BRACE MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	SERVO WEIGHT STANDARD <input checked="" type="checkbox"/> LOW PROFILE <input type="checkbox"/>	CHASSIS FLEX SCREW USED <input type="checkbox"/> SCREW NOT USED <input type="checkbox"/>