

XRAY XB4'21

FRONT

APPLIED ☒ APPLIED ☒

STEERING BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☒

LONGER BUSHINGS

UP ☐
DOWN ☒

SHIM mm

DRIVE SHAFT

CVD ☒ ECS ☐
Length 83 /mm

ROLL ENTER

REAR UPRIGHT

DRIVE SHAFT

Length 77 /mm

SHIM 3.5 mm

SHIMS /mm

HARD ☐
GRAPHITE ☐
ALU ☒

#325341 ADJ. DRIVE AXLE

1° ☐ 0.5° ☐

#107711 GAUGE

DOWNSTOP mm

DOWNSTOP mm

#107711 GAUGE

FRONT

CASTER

6° ☒
9° ☐
12° ☐

CASTER BLOCK

MEDIUM ☐
HARD ☒
GRAPHITE ☐
ALU ☐

WING CUTTING LINE

1 ☒ 2 ☐ 3 ☐ 4 ☐ 5 ☐

OFFSET

2 /slots

UPRIGHT WHEELBASE

SHIM /mm

IN FRONT OF ARM

WING SIDE LINE

HIGHER ☐
LOWER ☐

WING POSITION

UP ☐
MIDDLE ☐
DOWN ☐

WING THICKNESS

0.75 ☐ 1 ☒ 1.5 ☐

TYPE XB2

FF ☒ 1° ☐ 0.5° ☐
RF ☒ 1° ☐ 0.5° ☐
FR ☒ 1° ☐ 0.5° ☐
RR 2° ☒

ROLL CENTER

ECCENTRIC BUSHINGS

UP ☐ DOWN ☐

FRONT TOE

.5

OUT

STEER. PLATE

HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER

SHIM 5 mm
SHIM UNDER STEER. PLATE

SERVO SAVER

SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL

STANDARD ☐
GRAPHITE ☒

ARM SHIM mm

REAR TOE

IN

GRAPHITE FOR REAR BRACE

YES ☒
NO ☐

REAR BRACE

MEDIUM ☐
HARD ☒

ARM SHIM 1 mm

FRONT CAMBER

-2

FRONT DIFF HEIGHT

☒ ☐ ☐

DOWNSTOP

SHIM 1 mm

LENGTH

23 mm

UPSTOP

SHIM mm

COLLAR

STANDARD ☒ -2mm ☐

RIDE HEIGHT 15 mm

#107720 GAUGE

REAR DIFF HEIGHT

☒ ☐ ☐ ☐ ☐ ☐

REAR CAMBER

-2

DOWNSTOP

SHIM mm

LENGTH

30 mm

UPSTOP

SHIM mm

COLLAR

STANDARD ☒ -2mm ☐

RIDE HEIGHT 15 mm

FRONT ARMS

LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

T-BRACE

CHASSIS

STANDARD ☒
2.5mm ☐

REAR ARMS

LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

CHASSIS FLEX

SCREW USED ☒
SCREW NOT USED ☐

SIDE GUARDS

MEDIUM ☐
HARD ☒

XRAY 35g

FRONT

REAR