

XRAY XB4'21

FRONT

APPLIED ☒ APPLIED ☒

STEERING BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☒

LONGER BUSHINGS

UP ☐
DOWN ☒

SHIM

X mm

DRIVE SHAFT

CVD ☐ ECS ☒
Length 83 /mm

REAR UPRIGHT

DRIVE SHAFT

Length 75 /mm

SHIM

mm

SHIMS

2 /mm

HARD ☐
GRAPHITE ☐
ALU ☒

#325341 ADJ. DRIVE AXLE

1 2 3 4

1° ☒ 0.5° ☐

#107711 GAUGE

LOWER SHOCK POSITION

DOWNSTOP

mm

ROLL ENTER

DOWNSTOP

mm

#107711 GAUGE

FRONT

CASTER

6° ☒
9° ☐
12° ☐

CASTER BLOCK

MEDIUM ☒
HARD ☐
GRAPHITE ☐
ALU ☐

WING CUTTING LINE

1 2 3 4 5

WING SIDE LINE

HIGHER ☐
LOWER ☒

WING POSITION

UP ☐
MIDDLE ☐
DOWN ☒

WING THICKNESS

0.75 ☐ 1 ☒ 1.5 ☐

TYPE

TEC

OFFSET

2

BUMP STEER

SHIM 2 mm

UPRIGHT WHEELBASE

SHIM 1 /mm
IN FRONT OF ARM

FF

RF

FR

RR 2°

ROLL CENTER

ECCENTRIC BUSHINGS

1° ☒ 0.5° ☐
1° ☒ 0.5° ☐
UP ☒ DOWN ☐

FRONT TOE

OUT 1

STEER. PLATE

HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER

SHIM 4 mm

Servo SAVER

SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL

STANDARD ☐
GRAPHITE ☒

ARM SHIM

2 mm

REAR TOE

IN 2

GRAPHITE FOR REAR BRACE

YES ☒
NO ☐

REAR BRACE

MEDIUM ☐
HARD ☒

ARM SHIM

2 mm

FRONT CAMBER

1

FRONT DIFF HEIGHT

DOWNSTOP SHIM X mm
LENGTH 22 mm
UPSTOP SHIM 2 mm

COLLAR

STANDARD ☒ -2mm ☐

RIDE HEIGHT

13 mm

REAR DIFF HEIGHT

2

REAR CAMBER

DOWNSTOP SHIM 2 mm
LENGTH 27 mm
UPSTOP SHIM 2 mm

COLLAR

STANDARD ☐ -2mm ☒

RIDE HEIGHT

13 mm

FRONT ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

T-BRACE

CHASSIS

STANDARD ☒
2.5mm ☐

REAR ARMS

LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

CHASSIS FLEX

SCREW USED ☒
SCREW NOT USED ☐

SIDE GUARDS

MEDIUM ☐
HARD ☒

FRONT

REAR