

SET-UP SHEET

T4'21 SET-UP SHEET VER.1 ©XRAY

XRAY T4'21

RACE/TRACK	GT CHALLENGE
NAME	Marc Livermore
DATE	2021-05-03

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
2	1	9.21 /sec	/	

TRACK

TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
---------------	--	----------------------------------

TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
--------------	------------------------------------	---	-------------------------------

TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
----------	------------------------------	--	-------------------------------

FRONT TRANSMISSION REAR

SOLID AXLE	<input checked="" type="checkbox"/> YES
------------	---

GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL	10000 /cSt
-------------------------	------	-------------------------	------------

PINION	54 /T	SPUR GEAR	88 /T	FINAL DRIVE RATIO	3.09
--------	-------	-----------	-------	-------------------	------

FRONT SHOCKS REAR

ULTRA LOW PROFILE	<input checked="" type="checkbox"/>	SUPER LOW PROFILE	<input type="checkbox"/>	SHOCK TYPE		ULTRA LOW PROFILE	<input checked="" type="checkbox"/>	SUPER LOW PROFILE	<input type="checkbox"/>
-------------------	-------------------------------------	-------------------	--------------------------	------------	--	-------------------	-------------------------------------	-------------------	--------------------------

2.7	XRAY SPRINGS	2.7
-----	--------------	-----

450	OIL /cSt	425
-----	----------	-----

	REBOUND %	
--	-----------	--

<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO
------------------------------	--	--------------	------------------------------	--

<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> PSS	PISTONS	1.0mm	1.1mm	1.2mm	PROGRESSIVE
----------------------------------	----------------------------------	---	---------	-------	-------	-------	-------------

SHOCK LENGTH FRONT	8.5 /mm	SHOCK LENGTH REAR	9.0 /mm
--------------------	---------	-------------------	---------

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

GRAVITY USGT	TIRES
--------------	-------

SXT	ADDITIVE
-----	----------

2-3 MIN	ADDITIVE TIMING
---------	-----------------

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
------------	-------------	-----------	------------

TREATED AREA

FRONT	ROLL CENTER	REAR
-------	-------------	------

FF	FF	RR	RR
----	----	----	----

FR	FR	RF	RF
----	----	----	----

ARS - ACTIVE REAR SUSPENSION™

TOE GAIN	TOE LOSS	SHIM	SHIM	STEERING BLOCK
----------	----------	------	------	----------------

LINKS UP	LINKS DOWN	SHIMS	C-HUB	0°	2°	4°
----------	------------	-------	-------	----	----	----

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

STANDARD	OFFSET
----------	--------

FRONT	CASTER	0°	2°	4°	6°	SHIMS UNDER TOP DECK	NA /mm	REAR
SHIMS UNDER SHOCK	1	2	3	4	5	6	7	8
WHEELBASE /mm	5.2	5.2	5.2	5.2	5.2	5.2	5.2	5.2

TOE OUT	.8	ACKERMANN	NA /mm	FINAL TOE IN	3	OUTBOARD TOE	1	LOWER	NA /mm
SHIMS UNDER SHOCK	1	2	3	4	5	6	7	8	9
STEERING ARM	STANDARD	ALU	STEERING PLATE	YES	NO	STEERING PLATE	YES	NO	STEERING PLATE

DIFF POSITION	UP	DOWN	BALANCE	NA /g	BATT. BACKSTOP	COMPOSITE ADJ.	ALU	ALU ADJ.	BRASS ADJ.
STEERING SHIM	SHIM SIZE	KIT	BALANCE	NA /g	SERVO HORN	SERVO SAVER	ALU	SERVO HORN HEIGHT	TOP DECK
STEERING SHIM	SHIM SIZE	KIT	BALANCE	NA /g	SERVO HORN	SERVO SAVER	ALU	SERVO HORN HEIGHT	TOP DECK

STEERING LOCK	26 /deg.	CHASSIS	GRAPHITE	ALU	ALU-FLEX	OTHER	CHASSIS BRACE	BRASS	ALU
SERVO HOLDER	FORWARD	STANDARD	MOTOR MOUNT	YES	NO	CHASSIS BRACE	BRASS	ALU	ALU
STEERING PLATE	8mm	8.5mm	BATTERY PLATE	28 /g	RF	STD	.25	RF	STD

C-HUB	M	H	G	DRIVE SHAFT	53mm	52mm	51mm	50mm	DRIVE SHAFT	EC3	CVD	BEARING	BLADE
SHIM	2 /mm	SHIM	2 /mm	SHIM	1.5 /mm	SHIM	4 /mm	SHIM	4 /mm	SHIM	4 /mm	SHIM	4 /mm
STEER.BLOCK	M	H	G	ALU	STEER.BLOCK	M	H	G	ALU	STEER.BLOCK	M	H	G

FRONT	CAMBER	2 /deg.	SHOCK TOWERS	HIGHER SLP	STANDARD ULP	LOWER ULP	OTHER	REAR	CAMBER	2 /deg.	SHOCK TOWERS	HIGHER SLP	STANDARD ULP	LOWER ULP	OTHER
FRONT ARM	HARD (H)	GRAPHITE (G)	SHOCK TOWERS	HIGHER SLP	STANDARD ULP	LOWER ULP	OTHER	REAR ARM	HARD (H)	GRAPHITE (G)	SHOCK TOWERS	HIGHER SLP	STANDARD ULP	LOWER ULP	OTHER

COMMENTS
No Glue on front tires (wipe tires dry before race) - (28G SortaFast battery plate - 8G SortaFast ESC plate under ESC), 1 degree rear hubs, 10G HUDY Tungsten placed