








RACE	GTS Round 1											
TRACK	Vallelunga RC track											
NAME	Bruno Coelho					DATE						
TEMPERATURE AIR		35			TEMPERATURE TRACK		1					
LAPS		FINAL POS.	1	BEST LAPTIME	20.4 /sec	RACE LENGTH	45			/min		
TRACKS												
CONDITION		<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM		<input type="checkbox"/> BUMPY							
		<input checked="" type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED		<input type="checkbox"/> FAST							
TRACTION		<input type="checkbox"/> LOW		<input type="checkbox"/> MEDIUM		<input checked="" type="checkbox"/> HIGH						
1ST				GEARING				2ND				
PINION GEARS				SPUR GEARS				PINION GEARS				
<input type="checkbox"/> 15T	<input type="checkbox"/> 16T	<input type="checkbox"/> 17T	<input type="checkbox"/> 18T	⋮				<input type="checkbox"/> 19T	<input type="checkbox"/> 20T	<input type="checkbox"/> 21T		
<input type="checkbox"/> 48T	<input type="checkbox"/> 49T	<input checked="" type="checkbox"/> 50T	STANDARD	<input type="checkbox"/>	<input checked="" type="checkbox"/>	GRAPHITE	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	45T	46T	47T

CLUTCH			
STANDARD	<input checked="" type="checkbox"/>		SPRINGS TIGHTEN
OTHER	<input type="checkbox"/>		
SHOE	STD	STD	SPRING

FRONT		DIFFERENTIAL		REAR	
Gaphite 2Million		CASE MATERIAL OIL	Gaphite 150k2.7g		
13T <input checked="" type="checkbox"/> <input type="checkbox"/>	14T	BEVEL DRIVE GEAR	13T <input checked="" type="checkbox"/> <input type="checkbox"/>	14T	
46		CROWN GEAR	46		

FRONT		SHOCKS		REAR	
2 Dots 1 Stripe 800 /cSt Cell Soft /%		SPRINGS OIL MEMBRANE REBOUND PISTONS		3 Dots 800 /cSt Cell Soft /%	
<input checked="" type="checkbox"/>  6 HOLES <input type="checkbox"/>  8 HOLES <input type="checkbox"/>  10 HOLES	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	1.1 mm 1.2 mm 1.3 mm 1.4 mm	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	6 HOLES  <input checked="" type="checkbox"/> 8 HOLES  <input type="checkbox"/> 10 HOLES  <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
OTHER PISTONS					

FRONT	ANTI-ROLL BAR	REAR
2.4 /mm	 THICKNESS	3.0 /mm

ENGINE	
TYPE	FX G501
MUFFLER	FX 2168
MANIFOLD	FX 679700
PLUG	FX X7
FUEL	SRC 16%

BODY TYPE	TOTAL WEIGHT
Blitz Zonda	3510 /g

Pinion 14T/18T (Coming Soon)

FRONT

STEERING BLOCK

COMPOSITE ☐
ALU ☒

C-HUB

COMPOSITE ☐
ALU ☒
CASTER
16° ☐
6° ☒
2° ☐
GRAPHITE ☐

FRONT ARM

SOFT ☐
MEDIUM ☐
HARD ☒
GRAPHITE ☐

OFFSET

0 ☐ +1 ☒ -2 ☐

CASTER BUSHINGS

+2° ☐
+1° ☐
0° ☒
-1° ☐
-2° ☐

FRONT DROOP

27

REAR

REAR ARMS

MEDIUM ☐
HARD ☐
X-HARD ☒
GRAPHITE ☐

UPRIGHT

MEDIUM ☐
HARD ☐
GRAPHITE ☒

OFFSET

STANDARD ☐
+1 ☒ -2 ☐

REAR DROOP

27

UPPER SHOCK POSITION

REAR SHOCK PLATE POSITION

IN ☒ OUT ☐

MEASURE UNDER WHEEL AXLE #107717 GAUGE

FRONT

BUMP STEER SHIM

STEERING BLOCK /mm

STEERING PLATE **6** /mm

SHIMS PLACE ALWAYS UNDER

WHEELBASE SHIM POSITION

☒ 0 mm ☐ 2 mm

SHIMS BEHIND FRONT ARM

LOWER ROLL CENTER

FRONT **REAR**

1° ☒ **0.5°**

FR **RR**

REAR

WING HIGH **32** /mm

GRAPHITE BRACE

WITHOUT ☐

1-PIECE ☐

2-PIECES ☒

REAR DIFFUSOR

YES ☐ ☒ NO

WHEELBASE SHIM POSITION

☒ 2 mm ☐ 4 mm

SHIMS IN FRONT OF REAR ARM

RF **RR**

1° ☒ **0.5°**

FR **RR**

1° ☐ ☒ **0.5°**

1.5 FRONT TOE OUT

2.5 REAR TOE IN

ACKERMANN POSITION
3 2 1

TIGHTEN SERVO SAVER MATERIAL

TIGHT <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/>
MEDIUM <input type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>
SOFT <input type="checkbox"/>	

UPPER PLATE

COMPOSITE <input type="checkbox"/>
GRAPHITE <input type="checkbox"/>

WHEELBASE

0 mm	1 mm	2 mm	3 mm	4 mm
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

SHIMS IN FRONT OF UPRIGHT

TOP DECK

COMPOSITE <input type="checkbox"/>
GRAPHITE <input checked="" type="checkbox"/>

ENGINE MOUNT

STANDARD <input type="checkbox"/>
MONOBLOCK <input type="checkbox"/>

FRONT

2 FRONT CAMBER

LENGTH 22.3 mm

22.3 mm

9 /mm RIDE HEIGHT

10 /mm RIDE HEIGHT

2.5 REAR CAMBER

LENGTH 22.3 mm

22.3 mm

REAR