

SET-UP SHEET

XRAY GTXE'22 SET-UP VER. 01 ©XRAY

XRAY GTXE'22 C-HUB

RACE	GTS Round 1	
TRACK	Vallelunga RC track	
NAME	Bruno Coelho	DATE

TEMPERATURE AIR	35	TEMPERATURE TRACK	1st
-----------------	----	-------------------	-----

LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
	1st	19.6 /sec	5 /min

TRACKS			
CONDITION	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
	<input checked="" type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST

TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
----------	------------------------------	---------------------------------	-------------------------------

FRONT	DIFFERENTIAL		REAR
Graphite	CASE MATERIAL	Graphite	
500k	OIL	Graphite	
13T <input checked="" type="checkbox"/> 14T	BEVEL DRIVE GEAR	13T <input type="checkbox"/> 14T	
46T	CROWN GEAR	46T	

MOTOR PINION	GEARING	SPUR GEAR
20 /T		46 /T
STANDARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>		

FRONT	SHOCKS		REAR
2 Dots 1 Stripe	SPRINGS	3 Dots	
800 /cSt	OIL	800 /cSt	
Cell Soft	MEMBRANE	Cell Soft	
	REBOUND		
<input checked="" type="checkbox"/> 6 HOLES	PISTONS	<input checked="" type="checkbox"/> 6 HOLES	
<input type="checkbox"/> 8 HOLES	1.1 mm	<input checked="" type="checkbox"/> 1.2 mm	
<input type="checkbox"/> 10 HOLES	1.3 mm	<input type="checkbox"/> 1.4 mm	
OTHER PISTONS			

FRONT	ANTI-ROLL BAR		REAR
2.4 /mm	THICKNESS	2.8 /mm	

FRONT	TIRES		REAR
TIRES TYPE: PMT			
Q5	← COMPOUND →	Q3	
Q5	← COMPOUND →	Q3	

ELECTRONICS	
MOTOR	Hobbywing 2800W G2
SPEEDO	Hobbywing XR8 Pro G3
BATTERY TYPE	Sunpadow 8000mah Platinum

BODY	WEIGHT
TYPE Blitz Zonda	TOTAL 3710 /g

COMMENTS	
HW 30840000 Capacitor Module-E 2x WTF Fans 40mm 1x 30mm	

FRONT	C-HUB		FRONT ARM	REAR	
STEERING BLOCK	COMPOSITE <input checked="" type="checkbox"/>	ALU <input type="checkbox"/>	SOFT <input type="checkbox"/>	ANTI-ROLL BAR	
OFFSET	0 <input type="checkbox"/> +1 <input checked="" type="checkbox"/> +2 <input type="checkbox"/>	16° <input type="checkbox"/> 6° <input checked="" type="checkbox"/> 2° <input type="checkbox"/>	MEDIUM <input type="checkbox"/>	REAR ARMS	
CASTER BUSHINGS	+2° <input type="checkbox"/> +1° <input type="checkbox"/> 0° <input checked="" type="checkbox"/> -1° <input type="checkbox"/> -2° <input type="checkbox"/>	CASTER	HARD <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/>	
FRONT DROOP	27		GRAPHITE <input type="checkbox"/>	HARD <input type="checkbox"/>	
MEASURE UNDER WHEEL AXLE #107717 GAUGE			X-HARD <input checked="" type="checkbox"/>		
			GRAPHITE <input type="checkbox"/>		
			UPRIGHT		
			MEDIUM <input type="checkbox"/>		
			HARD <input checked="" type="checkbox"/>		
			GRAPHITE <input type="checkbox"/>		
			OFFSET		
			STANDARD <input type="checkbox"/>		
			+1 <input checked="" type="checkbox"/> +2 <input type="checkbox"/>		
			REAR DROOP		
			27		
			MEASURE UNDER WHEEL AXLE		

FRONT	SHOCKS		REAR
WING HIGH	32 /mm		
GRAPHITE BRACE	WITHOUT <input type="checkbox"/>		
1-PIECE <input type="checkbox"/>			
2-PIECES <input checked="" type="checkbox"/>			
REAR DIFFUSOR	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		
WHEELBASE SHIM POSITION	0 mm <input checked="" type="checkbox"/> 2 mm <input type="checkbox"/>		
SHIMS BEHIND FRONT ARM			
WHEELBASE SHIM POSITION	2 mm <input type="checkbox"/> 4 mm <input checked="" type="checkbox"/>		
SHIMS IN FRONT OF REAR ARM			
LOWER ROLL CENTER	1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>		
ECCENTRIC BUSHINGS			

FRONT	SERVO SAVER		REAR
1.5 FRONT TOE OUT	TIGHTEN	MATERIAL	2.5 REAR TOE IN
	TIGHT <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/>	
	MEDIUM <input type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>	
	SOFT <input type="checkbox"/>		
TOP DECK	COMPOSITE <input checked="" type="checkbox"/>		
GRAPHITE <input type="checkbox"/>			
WHEELBASE	0 mm <input type="checkbox"/> 1 mm <input type="checkbox"/> 2 mm <input checked="" type="checkbox"/> 3 mm <input type="checkbox"/> 4 mm		
SHIMS IN FRONT OF UPRIGHT			
STANDARD BATTERY	<input checked="" type="checkbox"/>		
BATTERY SETTING	FRONT <input type="checkbox"/> REAR <input type="checkbox"/>		
SHORT BATTERY	<input type="checkbox"/>		

FRONT	CAMBER		REAR
2.5 FRONT CAMBER			2.5 REAR CAMBER
LENGTH	22.3 mm		LENGTH
			22.5 mm
RIDE HEIGHT	8 /mm		RIDE HEIGHT
			10 /mm