

XRAY XB4'21

FRONT

APPLIED ☒ APPLIED ☒

STEERING BLOCK

MEDIUM ☐
HARD ☒
GRAPHITE ☐

LONGER BUSHINGS

UP ☒
DOWN ☐

SHIM

O mm

DRIVE SHAFT

CVD ☐ ECS ☒
Length 83 /mm

REAR UPRIGHT

DRIVE SHAFT

Length 75 /mm

SHIM

1 mm

SHIMS

2 /mm

HARD ☐
GRAPHITE ☐
ALU ☒

#325341 ADJ. DRIVE AXLE

1 2 3 4

1° ☒ 0.5° ☐

#107711 GAUGE

mm DOWNSTOP

#107701 SUPPORT BLOCKS

DOWNSTOP mm

#107711 GAUGE

FRONT

CASTER

6° ☐
9° ☒
12° ☐

CASTER BLOCK

MEDIUM ☐
HARD ☒
GRAPHITE ☐
ALU ☐

WING CUTTING LINE

1 2 3 4 5

OFFSET

1 /slots

UPRIGHT WHEELBASE

SHIM 3 /mm
IN FRONT OF ARM

WING SIDE LINE

HIGHER ☐
LOWER ☒

WING POSITION

UP ☐
MIDDLE ☒
DOWN ☐

WING THICKNESS

0.75 ☐ 1 ☒ 1.5 ☐

TYPE TEC

FF

1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

FR

1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

ROLL CENTER ECCENTRIC BUSHINGS

1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

RF

UP ☒ DOWN ☐

RR 2°

2° ☒

FRONT TOE

O

OUT

ALU STEERING PLATE #362574

ARM SHIM O mm

STEER. PLATE

HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER

SHIM 4 mm

Servo SAVER

SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL

STANDARD ☒
GRAPHITE ☐

REAR TOE

3

IN

#363242 PIVOT BALL ECCENTRIC

FRONT ☐ REAR ☐

GRAPHITE FOR REAR BRACE

YES ☒
NO ☐

REAR BRACE

MEDIUM ☐
HARD ☒

ARM SHIM 2 mm

FRONT CAMBER

1

DOWNSTOP

SHIM mm

LENGTH

24 mm

UPSTOP

SHIM mm

COLLAR

STANDARD ☒ -2mm ☐

FRONT DIFF HEIGHT

RIDE HEIGHT 16 mm

#107720 GAUGE

REAR DIFF HEIGHT

RIDE HEIGHT 16 mm

REAR CAMBER

1

DOWNSTOP

SHIM mm

LENGTH

29 mm

UPSTOP

SHIM 2 mm

COLLAR

STANDARD ☐ -2mm ☒

FRONT ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

T-BRACE

CHASSIS

STANDARD ☒
2.5mm ☐

REAR ARMS

LONG ☐
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

CHASSIS FLEX

SCREW USED ☒
SCREW NOT USED ☐

SIDE GUARDS

MEDIUM ☐
HARD ☐
Carbon

XRAY

35g

FRONT

REAR