

# SET-UP SHEET

# XRAY X1'20

RACE	BRCA National Rd2		
TRACK	Bedworth		
NAME	Luke Lee	DATE	04/07/2021
TEMPERATURE AIR		TEMPERATURE TRACK	
QUAL POSITION	1	FINAL POSITION	1
BEST LAP TIME	18.32 /sec	LAPS	16 / 306.58
TRACK			
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input checked="" type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
CENTER SHOCK ABSORBER			
SPRING	2.3	OIL /cSt	450
REBOUND %			
PISTON	<input type="checkbox"/> 3 HOLES	<input checked="" type="checkbox"/> 4 HOLES	
PISTON HOLES DIAMETER	<input checked="" type="checkbox"/> ø1.1mm	<input type="checkbox"/> ø1.2mm	<input type="checkbox"/> ø1.3mm
FOAM INSERT	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	
ANTI-ROLL BAR			
THICKNESS/mm			
SIDE DAMPING			
<input checked="" type="checkbox"/> SIDE TUBE			OIL 30K /cSt
<input type="checkbox"/> SIDE SHOCK			OIL /cSt
TIRES			
FRONT	Sweep Wets		REAR
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
ADDITIONAL TREATED AREA			
TRANSMISSION			
BALL DIFF	<input type="checkbox"/> LOOSE	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
SOLID AXLE	<input type="checkbox"/>		
GEAR DIFF	<input type="checkbox"/>	OIL /cSt	
GEARING			
PINION /T	39	SPUR GEAR /T	80
FINAL DRIVE RATIO	2.05		
ELECTRONICS			
MOTOR	Hobbywing G3R		
SPEEDO	Hobbywing Prostock		
BATTERIES	Sunpadow		
BODY			
EVO Race ER20			

FRONT		REAR	
BUMP STEER		SHOCK PYTE	
SHIM 4 /mm	SHIM nut/mm	SHORT	LONG
DROOP 3		4.2 FRONT RIDE HEIGHT	
MID RIDE HEIGHT 5.6		DROOP 2	
REAR RIDE HEIGHT 5.6			
WHEELBASE ADJUSTMENT			
LONG (+4mm) STANDARD (0mm) SHORT (-4mm)			
SHIM 1 /mm		ALU MOUNT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
SHIM 2.5 /mm		UPPER ARM SHIM 2 /mm	
SHIM 0.5 /mm		LUBE 10K /cSt	
SHIM 0.5 /mm		SPRING 1.5	
SHIM 0.5 /mm		LOWER ARM SHIM /mm	
SIDE SPRING		RIDE HEIGHT SHIM /mm	
SILVER C=0.6		GOLD C=0.9	
BLACK C=1.2		SILVER C=1.5	
GOLD C=1.8		WING SHIM /mm	
CAMBER			
1.0° 1.5° 2.0° 2.5°			
CASTER			
3° 6° 9° 12°			
LOWER ARMS			
STANDARD GRAPHITE <input checked="" type="checkbox"/>			
SOFT GRAPHITE ARMS <input type="checkbox"/>			
ARM MOUNT PLATE			
STANDARD <input checked="" type="checkbox"/>			
WIDE <input type="checkbox"/>			
CHASSIS			
GRAPHITE 2.5mm (KIT) <input checked="" type="checkbox"/>			
HARD GRAPHITE <input type="checkbox"/>			
ALU <input type="checkbox"/>			
ALU FLEX <input type="checkbox"/>			
BATTERY POSITION			
<input type="checkbox"/> INLINE			
<input checked="" type="checkbox"/> CROSS CHASSIS			
REAR WING			
STANDARD <input checked="" type="checkbox"/>			
OTHER:			
REAR AXLE			
STEEL <input checked="" type="checkbox"/>			
GRAPHITE <input type="checkbox"/>			
ADJUSTABLE <input type="checkbox"/>			
WING POSITION			
1 2 3			
TOE			
OUT 1.5 /deg.			
GRAPHITE BRACE			
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
SHIM USED			
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>			
FRONT SPOILER			
LOW DOWNFORCE <input type="checkbox"/>			
HIGH DOWNFORCE <input type="checkbox"/>			
STEERING ANGLE			
25 /°			
FRONT WIDTH			
SHIM 0.6 /mm			
TOP DECK			
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
TOP DECK FLEX			
SOFT <input checked="" type="checkbox"/>			
MEDIUM <input type="checkbox"/>			
STIFF <input type="checkbox"/>			
REAR WIDTH			
SHIM 3 /mm			
REAR WING POSITION			
Left = Right			
1 2 3 4 5 6			

COMMENTS Wet Setup