

SET-UP SHEET

XRAY GTX8'22 SET-UP VER. 01 ©XRAY

XRAY GTX8'22 C-HUB

RACE	Campeonato de España 2021		
TRACK	Elechas		
NAME	Toni Santana	DATE	18-7-2021
TEMPERATURE AIR	28°	TEMPERATURE TRACK	
LAPS	FINAL POS.	BEST LAPTIME	/sec
		RACE LENGTH	/min
TRACKS			
CONDITION	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
GEARING			
1ST		2ND	
<input type="checkbox"/> 15T	<input checked="" type="checkbox"/> 16T	<input type="checkbox"/> 19T	<input type="checkbox"/> 20T
<input type="checkbox"/> 17T	<input type="checkbox"/> 18T	<input type="checkbox"/> 21T	<input type="checkbox"/> 22T
SPUR GEARS			
<input type="checkbox"/> 48T	<input checked="" type="checkbox"/> 49T	<input type="checkbox"/> 45T	<input type="checkbox"/> 46T
<input type="checkbox"/> 50T	<input type="checkbox"/> STANDARD	<input type="checkbox"/> GRAPHITE	<input type="checkbox"/> 47T
CLUTCH			
CLUTCH	STANDARD <input checked="" type="checkbox"/>		
SHOE	STD		
	348541		
DIFFERENTIAL			
FRONT	CASE MATERIAL		REAR
STD	OIL		STD
2.000.000	80.000		
<input checked="" type="checkbox"/> 13T	<input type="checkbox"/> 14T	BEVEL DRIVE GEAR	<input checked="" type="checkbox"/> 13T
46		CROWN GEAR	46
SHOCKS			
FRONT	SPRINGS		REAR
STD	OIL		STD
800	800		
STD	MEMBRANE		STD
10	10		
<input checked="" type="checkbox"/> 6 HOLES	<input checked="" type="checkbox"/> 1.1 mm	<input checked="" type="checkbox"/> 6 HOLES	<input checked="" type="checkbox"/> 1.1 mm
<input type="checkbox"/> 8 HOLES	<input type="checkbox"/> 1.2 mm	<input type="checkbox"/> 8 HOLES	<input type="checkbox"/> 1.2 mm
<input type="checkbox"/> 10 HOLES	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/> 10 HOLES	<input type="checkbox"/> 1.3 mm
	<input type="checkbox"/> 1.4 mm		<input type="checkbox"/> 1.4 mm
ANTI-ROLL BAR			
FRONT	THICKNESS		REAR
2.5	2.8		
TIRES			
TIRES TYPE: PMT			
FR	Q7		RR
	Q5		
ENGINE			
TYPE	REDS 521 GTS PRO TUNED		
MUFFLER	HIPEX 2115		
MANIFOLD	HIPEX CL210172 - B5		
PLUG	TS7		
FUEL	MERLIN ADVANCE		
BODY TYPE		TOTAL WEIGHT	
GT5		3575	
COMMENTS			

FRONT		REAR	
STEERING BLOCK	C-HUB	FRONT ARM	REAR ARMS
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	SOFT <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
ALU <input checked="" type="checkbox"/>	ALU <input checked="" type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>	HARD <input checked="" type="checkbox"/>
	CASTER	HARD <input type="checkbox"/>	X-HARD <input type="checkbox"/>
	16° <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>
	6° <input checked="" type="checkbox"/>		
	2° <input type="checkbox"/>		
OFFSET			
0 <input type="checkbox"/>			
+1 <input type="checkbox"/>			
+2 <input checked="" type="checkbox"/>			
CASTER BUSHINGS			
+2° <input type="checkbox"/>			
+1° <input checked="" type="checkbox"/>			
0° <input type="checkbox"/>			
-1° <input type="checkbox"/>			
-2° <input type="checkbox"/>			
FRONT DROOP			
7			
MEASURE UNDER WHEEL AXLE #107717 GAUGE		MEASURE UNDER WHEEL AXLE #107717 HUDY GAUGE	

FRONT		REAR	
BUMP STEER SHIM		WING HIGH	
STEERING BLOCK /mm		/mm	
STEERING PLATE 6 /mm			
SHIMS PLACE ALWAYS UNDER			
WHEELBASE SHIM POSITION		WHEELBASE SHIM POSITION	
<input checked="" type="checkbox"/> 0mm <input type="checkbox"/> 2mm		<input checked="" type="checkbox"/> 2mm <input type="checkbox"/> 4mm	
SHIMS BEHIND FRONT ARM		SHIMS IN FRONT OF REAR ARM	
FF		RF	
FR		RR	
1° <input type="checkbox"/> 0.5° <input type="checkbox"/>		1° <input type="checkbox"/> 0.5° <input type="checkbox"/>	
1° <input type="checkbox"/> 0.5° <input type="checkbox"/>		1° <input type="checkbox"/> 0.5° <input type="checkbox"/>	
LOWER ROLL CENTER		REAR	
ECCENTRIC BUSHINGS			
GRAPHITE BRACE		REAR DIFFUSOR	
WITHOUT <input type="checkbox"/>		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	
1-PIECE <input type="checkbox"/>			
2-PIECES <input checked="" type="checkbox"/>			

FRONT		REAR	
1.5° FRONT TOE OUT		3° REAR TOE IN	
TIGHTEN SERVO SAVER MATERIAL		UPPER PLATE	
TIGHT <input checked="" type="checkbox"/>		COMPOSITE <input type="checkbox"/>	
MEDIUM <input type="checkbox"/>		GRAPHITE <input type="checkbox"/>	
SOFT <input type="checkbox"/>			
WHEELBASE		ENGINE MOUNT	
0mm <input type="checkbox"/> 1mm <input checked="" type="checkbox"/> 2mm <input type="checkbox"/> 3mm <input type="checkbox"/> 4mm		STANDARD <input type="checkbox"/>	
SHIMS IN FRONT OF UPRIGHT		MONOBLOCK <input checked="" type="checkbox"/>	
ACKERMANN POSITION			
3 2 1			
TOP DECK			
COMPOSITE <input type="checkbox"/>			
GRAPHITE <input checked="" type="checkbox"/>			

FRONT		REAR	
2.5°-3° FRONT CAMBER		REAR CAMBER 3°-3.5°	
LENGTH		LENGTH	
mm		mm	
RIDE HEIGHT		RIDE HEIGHT	
8		9.5	
/mm		/mm	