SET-UP SHEET

XT2'21 SET-UP SHEET VER. 1 ©XRAY 2020

XRAY XT2'21

RACE	Longfield Six Days Rd3
TRACK	
NAME	DATE 12.12.2021

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	1	FINAL POSITION	

TRACK

SIZE	☐ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	VERY-LOW	MEDIUM	VERY-HIGH
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ CLAY	☒ CARPET	☐ ASTRO
CONDITION	☐ BLUE GROOVE / ☐ DUSTY	☐ HARD PACKED / ☐ LOAMY	☒ DRY / ☐ WET

TRANSMISSION

DIFFERENTIAL	BALL DIFF ☐	☒ GEAR DIFF	OIL 10k cSt
SATELITE GEARS	COMPOSITE ☐	☒ STEEL	GEARS 2 ☒ 4 ☐
SLIPPER	2 PAD ☐	☒ 3 PAD	mm
	ELIMINATOR ☐		

GEARING

PINION	19 T	SPUR GEAR	78 T

SHOCKS

FRONT		REAR
4	SPRINGS	3
cSt 550	OIL	400 cSt
☒ 2 HOLES / ☐ 3 HOLES / ☐ 6 HOLES / ☐ HOLES	PISTONS: ☐ ø1.2mm, ☐ ø1.3mm, ☐ ø1.4mm, ☒ ø1.6mm, ☐ ø1.7mm	☐ 2 HOLES / ☐ 3 HOLES / ☒ 6 HOLES / ☐ HOLES
DOWNSTOP SHIM mm (INSERT UNDER PISTON)		DOWNSTOP SHIM mm (INSERT UNDER PISTON)
LENGTH mm		LENGTH mm
UPSTOP SHIM mm (INSERT ABOVE COLLAR)		UPSTOP SHIM 2 mm (INSERT ABOVE COLLAR)
KIT ☐ — BALL JOINT — ☒ KIT		
Long		

ANTI ROLL BARS

FRONT	THICKNESS	REAR
1.8 mm		1.2 mm

TIRES

FRONT		REAR
Swagger	BRAND	Minipin
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS

MOTOR	Absima 6.5	Absima CTS 1	SPEEDO
MOTOR TIMING		Absima 5800	BATTERY

BODY

1mm ☒ ☐ 0.75mm LIGHT OTHER

COMMENT

FRONT / REAR

APPLIED ◉ ☒ APPLIED

- LONGER BUSHINGS: ☐ UP ☒ DOWN
- STEERING BLOCK: ☐ MEDIUM ☒ HARD ☐ GRAPHITE
- CASTER BLOCK: ☐ MEDIUM ☐ HARD ☒ GRAPHITE
- SHIM 2 mm
- CAMBER LINK LOCATION 2 1
- LOWER SHOCK POSITION 3 2 1
- UPPER SHOCK POSITION 3 2 1
- SHIM 2 mm
- DRIVE SHAFT: ☐ CVD ☐ ECS Lenght /mm
- SHIM 2 mm
- SHIM /mm
- ☐ HARD ☐ GRAPHITE ☐ ALU
- #325341 ADJ. DRIVE AXLE 1 2 3 4
- 1 2 LOWER SHOCK POSITION
- ☐ 0.5° ☐ 1°

REAR

- CASTER BUSHINGS: 0° ☐ 2.5° ☒ 5° ☐ OTHER
- CASTER
- KICK-UP ANGLE: 23° ☐ KIT 26° ☒ 29° ☐
- BUMP STEER SHIM /mm
- STEERING
- STEERING ARMS: ☐ COMPOSITE ☐ ALU
- CARPET ☒ / DIRT ☐
- SHIMS /mm
- STEERING PLATE: ☐ COMPOSITE ☐ ALU
- ROLL CENTER ECCENTRIC BUSHINGS
- RF: 1° ☐ ☒ 0.5°
- RR: 1° ☒ ☐ 0.5°

FRONT / REAR

- 1 ° FRONT TOE
- OUT
- OFFSET 2 SLOTS
- WHEELBASE SHIM 0mm ☐ ☒ 1mm (IN FRONT OF ARM)
- EXTENSION: ☐ 0 SLOTS ☐ 1 SLOT ☐ 2 SLOTS ☐ 3 SLOTS
- REAR TOE ° IN
- OFFSET SLOTS
- WHEELBASE SHIM /mm (IN REAR OF ARM)
- BATTERY PLACEMENT: LONG SIDE FRONT 1 2 3 / LONG SIDE REAR
- ROLL CENTER
- ROLL CENTER HOLDER: ☐ MEDIUM ☐ HARD ☒ ALU
- GUARD BRACE FLEX
- BATTERY SIZE: ☒ STD. SHORT ☐ LOW SHORT
- UPPER BRACE: YES ☐ ☒ NO
- UPPER DECK: ☐ MEDIUM ☐ HARD
- 1 2 3 4 5 6 7 8
- SERVO HORNS SHIM 10 /mm
- COMPOSITE / ROLL CENTER / ALU

FRONT / REAR

- FRONT CAMBER 2 °
- REAR CAMBER 2 °
- DIFF HEIGHT
- FRONT ARM: ☐ MEDIUM ☐ HARD ☒ GRAPHITE
- REAR ARM: ☐ MEDIUM ☐ HARD ☒ GRAPHITE
- RIDE HEIGHT 20 mm
- RIDE HEIGHT #107721 GAUGE
- RIDE HEIGHT 19 mm

FRONT / REAR

- ARM MOUNT: ☐ COMPOSITE ☒ ALU ☐ BRASS
- ARM SHIM /mm
- SERVO POSITION 1 2 3
- BALANCE g
- BALANCE 35 g
- CHASSIS BRACE: ☐ MEDIUM ☒ HARD
- SERVO WEIGHT: ☒ STANDARD ☐ LOW PROFILE
- CHASSIS: ☒ ALU (OTHER)
- CHASSIS FLEX: ◉ SCREW USED ○ SCREW NOT USED
- WING: ☐ HIGH ☐ LOW (OTHER /mm)
- HIGH