

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	Ets round 4 Neumunster		
TRACK			
NAME	Duchet Alexandre	DATE	

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
			/sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT

TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST
--------------	------------------------------------------------------------------------------------------------------------

TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH
----------	-------------------------------------------------------------------------------------------------------

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	

GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL	7000 /cSt
-------------------------	------	-------------------------	-----------

PINION	100 /T	SPUR GEAR	38 /T	FINAL DRIVE RATIO	5
--------	--------	-----------	-------	-------------------	---

FRONT	SHOCKS	REAR
2.5/2.8	XRAY SPRINGS	2.6
425	OIL /cSt	425
	REBOUND %	

<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
---------------------------------------------------------------------	--------------	---------------------------------------------------------------------

<input type="checkbox"/> 3 HOLES	PISTONS	3 HOLES <input type="checkbox"/>
<input type="checkbox"/> 4 HOLES	1.0mm	4 HOLES <input type="checkbox"/>
<input checked="" type="checkbox"/> PSS	1.1mm	PSS <input checked="" type="checkbox"/>
	1.2mm	

SHOCK LENGTH FRONT	9 /mm	SHOCK LENGTH REAR	8,5 /mm
--------------------	-------	-------------------	---------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Matrix 28	TIRES	Matrix 28
V4	ADDITIVE	V4
15	ADDITIVE TIMING	15

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1325 /g	WEIGHT BALANCE	FRONT 49 % REAR 51 %
--------------	---------	----------------	----------------------

MOTOR	Orca	TIMING	
-------	------	--------	--

ESC	Orca	BATTERIES	Orca 6090
-----	------	-----------	-----------

BODY		WING	
------	--	------	--

64 /mm	Dimension from body post to window bottom line	BODY POSITION
6 +2mm /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
66 /mm	Dimension from edge to surface	

COMMENTS

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER	TOE GAIN	RIDE HEIGHT
Adjust with eccentric bushings	4 /mm	19 /mm	8 /mm		Adjust with eccentric bushings	5 /mm	
2.5 /mm FF	5 /mm	FR 2.5 /mm	<input type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN		3 /mm RF	5.2 /mm	RR 3 /mm

2 /deg. CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
	/mm	1.5 /mm SHIM 2 /mm	SHIM 0.5 /mm
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/>	
		DRIVE SHAFT 58mm 59mm STD. BEARING	
		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	6.6 /mm DOWNSTOP

2 /deg. CAMBER	BODY POST	REAR SUSPENSION	REAR HUB
Left = Right	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SHOCK POSITION	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		1.5 /mm SHIM 2 /mm	SHIM 1.5 /mm
		DRIVE SHAFT 52mm 54mm STD. BEARING	
		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	4 /mm DOWNSTOP

1 TOE OUT	ACKERMANN	SHIM	2.5 TOE IN
Left = Right	SHIM 1 /mm	1 /mm	Left = Right
DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>			DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
UPPER ARM STANDARD <input checked="" type="checkbox"/>	STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/>	UPPER ARM STANDARD <input checked="" type="checkbox"/>
OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/>	TOP DECK <input checked="" type="checkbox"/> SPLITTED <input type="checkbox"/>	TOP DECK 1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/>	OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/>
SHIM/mm			SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 7.5 /mm	MOTOR MOUNT
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	CHASSIS T-BRACE
FR SERVO HOLDER	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/>
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	