

XRAY XB4'22

FRONT

ALU C-HUB SHIM
UP /mm
DOWN /mm

LONGER BUSHINGS
UP ☐
DOWN ☒

DRIVE SHAFT
CVD ☒ ECS ☐
Lenght 83 /mm

SHIM
2 mm

STEERING BLOCK
MEDIUM ☐
HARD ☒
GRAPHITE ☐

LOWER SHOCK POSITION

DOWNSTOP mm

#107711 GAUGE

REAR UPRIGHT

DRIVE SHAFT
Lenght 77 /mm

SHIM
2 mm

SHIMS 1 /mm

HARD ☒
GRAPHITE ☐
ALU ☐

ROLL ENTER

DOWNSTOP mm

#107711 GAUGE

CASTER
6° ☐
7° ☐
9° ☒
12° ☐

CASTER BLOCK
MEDIUM ☐
HARD ☒
GRAPHITE ☐
ALU ☐

WING CUTTING LINE
1 2 3 4 5

OFFSET
3 /slots

UPRIGHT WHEELBASE
SHIM 1 /mm
IN FRONT OF ARM

WING SIDE LINE
HIGHER ☐
LOWER ☒

WING POSITION
UP ☐
MIDDLE ☒
DOWN ☐

WING THICKNES
0.75 ☐ 1 ☒ 1.5 ☐

TYPE Kit

FF ☒ 1°
☐ 0.5°

RF ☒ 1°
☐ 0.5°

FR ☒ 1°
☐ 0.5°

RR 2° ☒

ROLL CENTER
ECCENTRIC BUSHINGS

UP ☒ **DOWN** ☐

FRONT TOE
OUT 1

ARM SHIM
2 mm

STEER. PLATE
HARD ☒
GRAPHITE ☐
ALU ☐
BUMP STEER
SHIM 5 mm
SHIM UNDER STEER. PLATE

SERVO SAVER
SOFT ☐
MEDIUM ☐
TIGHT ☒
MATERIAL
STANDARD ☒
GRAPHITE ☐

REAR TOE
IN 2

GRAPHITE FOR REAR BRACE
YES ☒
NO ☐

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM
2 mm

FRONT CAMBER
2

DOWNSTOP
SHIM 1 mm

LENGTH
22 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☒ -2mm

FRONT DIFF HEIGHT
RIDE HEIGHT 13 mm

REAR DIFF HEIGHT
RIDE HEIGHT 13 mm

REAR CAMBER
2

DOWNSTOP
SHIM 2 mm

LENGTH
27 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☐ -2mm

FRONT ARMS
LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☒
GRAPHITE ☐

BALANCE
g

SIDE GUARDS
HARD ☒
GRAPHITE ☐

REAR ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☒
GRAPHITE ☐

CHASSIS FLEX
SCREW USED ☒
SCREW NOT USED ☐

T-BRACE

FRONT BATTERY POST

REAR BATTERY POST

BALANCE
g

BALANCE
g

XRAY
35g

FRONT

REAR