

XRAY XB4'22

FRONT

ALU C-HUB SHIM
UP /mm
DOWN /mm

LONGER BUSHINGS
UP ☒
DOWN ☐

DRIVE SHAFT
CVD ☒ ECS ☐
Length /mm

SHIM
2 mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☒

LOWER SHOCK POSITION

DOWNSTOP
#107711 GAUGE

REAR UPRIGHT

DRIVE SHAFT
Length 77 /mm

SHIM
2 mm

SHIMS
2 /mm

HARD GRAPHITE ALU
☒

#325341 ADJ. DRIVE AXLE
1 2 3 4

ROLL ENTER

DOWNSTOP
#107711 GAUGE

CASTER
6° ☐
7° ☐
9° ☒
12° ☐

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☒
ALU ☐

WING CUTTING LINE
1 2 3 4 5

WING SIDE LINE
HIGHER ☒
LOWER ☐

WING POSITION
UP ☒
MIDDLE ☐
DOWN ☐

WING THICKNESSES
0.75 ☒
1 ☐
1.5 ☐

TYPE
TEC

OFFSET
2

BUMP STEER
SHIM 2 mm

UPRIGHT WHEELBASE
SHIM /mm

IN FRONT OF ARM

FF
1° ☒
0.5° ☐

RF
1° ☒
0.5° ☐

FR
1° ☒
0.5° ☐

RR 2°
UP ☒
DOWN ☐

ROLL CENTER ECCENTRIC BUSHINGS

FRONT TOE
OUT 1

STEER. PLATE
HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER
SHIM 2 mm
SHIM UNDER STEER. PLATE

SERVO SAVER
SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL
STANDARD ☐
GRAPHITE ☒

ARM SHIM
2 mm

REAR TOE
IN

GRAPHITE FOR REAR BRACE
YES ☐
NO ☒

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM
0 mm

FRONT CAMBER
2

DOWNSTOP
SHIM 0 mm

LENGTH
22 mm

UPSTOP
SHIM 1 mm

COLLAR
STANDARD ☒ -2mm

FRONT DIFF HEIGHT
RIDE HEIGHT

REAR DIFF HEIGHT
RIDE HEIGHT

REAR CAMBER
2

DOWNSTOP
SHIM 0 mm

LENGTH
29 mm

UPSTOP
SHIM 1 mm

COLLAR
STANDARD ☒ -2mm

FRONT ARMS
LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

BALANCE
0 g

SIDE GUARDS
HARD ☐
GRAPHITE ☐

BALANCE
0 g

REAR ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

T-BRACE

FRONT BATTERY POST

REAR BATTERY POST

BALANCE
0 g

BALANCE
0 g

CHASSIS FLEX
SCREW USED ☒
SCREW NOT USED ☐