

**XRAY XB4'22**

**FRONT**

**ALU C-HUB SHIM**  
UP /mm  
DOWN /mm

**LONGER BUSHINGS**  
UP ☒  
DOWN ☐

**DRIVE SHAFT**  
CVD ☒ ECS ☐  
Lenght 83 /mm

**SHIM**  
O mm

**STEERING BLOCK**  
MEDIUM ☐  
HARD ☒  
GRAPHITE ☐

**LOWER SHOCK POSITION**

**DOWNSTOP**  
#107711 GAUGE

**REAR UPRIGHT**

**DRIVE SHAFT**  
Lenght 77 /mm

**SHIM**  
2 mm

**SHIMS** 2 /mm

**HARD** ☒  
**GRAPHITE** ☐  
#325341 ADJ. DRIVE AXLE

**ROLL ENTER**

**DOWNSTOP**  
#107711 GAUGE

**CASTER**  
6° ☐  
7° ☒  
9° ☐  
12° ☐

**CASTER BLOCK**  
MEDIUM ☐  
HARD ☒  
GRAPHITE ☐  
ALU ☐

**WING CUTTING LINE**  
1 2 3 4 5

**OFFSET**  
2 /slots

**UPRIGHT WHEELBASE**  
SHIM 3 /mm  
IN FRONT OF ARM

**WING SIDE LINE**  
HIGHER ☐  
LOWER ☒

**WING POSITION**  
UP ☐  
MIDDLE ☒  
DOWN ☐

**WING THICKNES**  
0.75 ☐ 1 ☒ 1.5 ☐

**TYPE** TEC

**FF** ☒ 1°  
☐ 0.5°

**RF** ☒ 1°  
☐ 0.5°

**FR** ☒ 1°  
☐ 0.5°

**RR** 2° ☒  
UP ☒ DOWN ☐

**FRONT TOE**  
OUT 1

**STEER. PLATE**  
HARD ☐  
GRAPHITE ☒  
ALU ☐  
BUMP STEER  
SHIM 2 mm  
SERVO SAVER  
SOFT ☐  
MEDIUM ☐  
TIGHT ☒  
MATERIAL  
STANDARD ☐  
GRAPHITE ☒

**ARM SHIM**  
O mm

**REAR TOE**  
IN 2

**GRAPHITE FOR REAR BRACE**  
YES ☒  
NO ☐

**REAR BRACE**  
MEDIUM ☐  
HARD ☒

**ARM SHIM**  
2 mm

**FRONT CAMBER** 2

**DOWNSTOP**  
SHIM O mm

**LENGTH** 22,5 mm

**UPSTOP**  
SHIM O mm

**COLLAR**  
STANDARD ☒ -2mm

**FRONT DIFF HEIGHT**  
RIDE HEIGHT 16 mm

**REAR DIFF HEIGHT**  
RIDE HEIGHT 16 mm

**REAR CAMBER** 2

**DOWNSTOP**  
SHIM O mm

**LENGTH** 29,5 mm

**UPSTOP**  
SHIM O mm

**COLLAR**  
STANDARD ☒ -2mm

**FRONT ARMS**  
LONG ☐  
SHORT ☒  
MEDIUM ☐  
HARD ☒  
GRAPHITE ☐

**BALANCE** g

**SIDE GUARDS**  
HARD ☒  
GRAPHITE ☐

**REAR ARMS**  
LONG ☒  
SHORT ☐  
MEDIUM ☐  
HARD ☒  
GRAPHITE ☐

**CHASSIS FLEX**  
SCREW USED ☒  
SCREW NOT USED ☐

**FRONT BATTERY POST**

**REAR BATTERY POST**

**BALANCE** g

**BALANCE** g

**FRONT**

**REAR**