

# SET-UP SHEET

VER.01 ©XRAY

**XRAY X4F'23**

RACE	ETS R2 Aigen-Schlägel		
TRACK	MAV Aigen		
NAME	Jacques Libar	DATE	21-24/07/2022

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
50-60	7	7	22.2 /sec	/ /	/

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL	100K /cSt	

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
38	90	4.5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.5-2.8
450	OIL /cSt	450
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> 1.0mm	<input type="checkbox"/> 3 HOLES
<input checked="" type="checkbox"/> 4 HOLES	<input type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input checked="" type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS

SHOCK LENGTH FRONT	SHOCK LENGTH REAR
9.5 /mm	9.5 /mm

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Ride ETS silver	TIRES	Ride ETS silver
MR33	ADDITIVE	MR33
30 min	ADDITIVE TIMING	30 min

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT 63 % REAR 37 %
--------------	---------	----------------	----------------------

MOTOR	HW 17.5 ETS	TIMING
-------	-------------	--------

ESC	HW ETS Limiter	BATTERIES	Team Zombie 4400
-----	----------------	-----------	------------------

BODY	Blitz YRS	WING	kit
------	-----------	------	-----

<p>Dimension from body post to window bottom line</p> <p>Dimension from body post to upper holder</p> <p>WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/></p> <p>Dimension from edge to surface</p>	BODY POSITION
---	---------------

COMMENTS
100g in Bumper

FRONT & REAR SUSPENSION	
<b>FRONT CASTER</b> <input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings 	<b>REAR CASTER</b> <input type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input checked="" type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings 
<b>BUMP STEER</b> 3 /mm <b>HEIGHT</b> 19 /mm <b>SHIM</b> 4 /mm <b>TOE GAIN</b> 3.5 /mm <b>FRIDE HEIGHT</b> 2.5 /mm <b>FR 2.5 /mm</b> <input type="checkbox"/> SERVO SAVER <input checked="" type="checkbox"/> SERVO HORN	<b>TOE GAIN</b> 3.5 /mm <b>RF 3.5 /mm</b> <b>RR 3.5 /mm</b> <b>FRIDE HEIGHT</b> 6.0 /mm <b>RR 3.5 /mm</b>

<b>2.0 /deg. CAMBER</b> Left = Right 	<b>FRONT SUSPENSION</b> <b>FRONT BRACE</b> YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> <b>BULKHEAD SHIMS</b> YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <b>DRIVE SHAFT</b> <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> STD. BEARING <b>FRONT HUB</b> COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> <b>SHIM</b> 0.5 /mm <b>DOWNSTOP</b> 5.2 /mm
---	--

<b>2.0 /deg. CAMBER</b> Left = Right 	<b>REAR SUSPENSION</b> <b>REAR SHOCK POSITION</b> 1 2 3 4 <b>SHIM</b> 1.5 /mm <b>DOWNSTOP</b> 3.8 /mm
---	---

<b>0.5 TOE OUT</b> Left = Right 	<b>FRONT TOP VIEW</b> <b>ACKERMANN</b> SHIM 1 /mm <b>DIFF POSITION</b> UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> <b>UPPER ARM</b> STANDARD <input checked="" type="checkbox"/> <b>OFFSET</b> STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm <b>TOP DECK</b> <input checked="" type="checkbox"/> SPLITTED	<b>1 TOE IN</b> Left = Right 	<b>REAR TOP VIEW</b> <b>UPPER ARM</b> STANDARD <input checked="" type="checkbox"/> <b>OFFSET</b> STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm <b>TOP DECK CUTTING</b>
--	--	-------------------------------------	---

<b>FRONT BOTTOM VIEW</b> <b>STEER. LOCK</b> 25 /deg. <b>STEER. SHIM</b> SIZE 7.5 /mm <b>FRONT BRACE</b> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> <b>FRONT ARMS</b> MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> <b>STEER. PLATE</b> STANDARD <input checked="" type="checkbox"/> <input type="checkbox"/>	<b>REAR BOTTOM VIEW</b> <b>T-BRACE</b> ALU <input type="checkbox"/> BRASS <input type="checkbox"/> <b>MOTOR MOUNT</b> CHASSIS T-BRACE <b>REAR ARMS</b> MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> <b>CHASSIS</b> GRAPHITE <input checked="" type="checkbox"/>
--	---