

SET-UP SHEET

XRAY GTXE'22 SET-UP VER. 01 ©XRAY

XRAY GTXE'22 C-HUB

RACE	2 Campeonato España	
TRACK	Club Charro Salamanca	
NAME	Luis Moreno	DATE 25/07/2022

TEMPERATURE AIR	42	TEMPERATURE TRACK	
-----------------	----	-------------------	--

LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
		20.0 /sec	/min

TRACKS			
CONDITION	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY
	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST

TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
----------	------------------------------	--	-------------------------------

FRONT	DIFFERENTIAL		REAR
Graphite	CASE MATERIAL	Graphite	
300000	OIL	Graphite	
13T <input checked="" type="checkbox"/> 14T	BEVEL DRIVE GEAR	13T <input type="checkbox"/> 14T	
46	CROWN GEAR	46	

MOTOR PINION	GEARING	SPUR GEAR
20 /T		45 /T
STANDARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>		

FRONT	SHOCKS		REAR
3 dot 1	SPRINGS	3 dot	
600 /cSt	OIL	700 /cSt	
Std	MEMBRANE	Std	
15 /%	REBOUND	15 /%	
<input checked="" type="checkbox"/> 6 HOLES	PISTONS	<input checked="" type="checkbox"/> 6 HOLES	
<input type="checkbox"/> 8 HOLES	1.1 mm	<input checked="" type="checkbox"/> 8 HOLES	
<input type="checkbox"/> 10 HOLES	1.2 mm	<input type="checkbox"/> 10 HOLES	
	1.3 mm		
	1.4 mm		
OTHER PISTONS			

FRONT	ANTI-ROLL BAR	REAR
2 /mm	THICKNESS	2.4 /mm

FRONT	TIRES	REAR
TIRES TYPE: PMT		
Q5	← COMPOUND →	Q3
Q5	← COMPOUND →	Q3

ELECTRONICS	
MOTOR	Hw 2400kw
SPEEDO	Hw
BATTERY TYPE	9500 XTR

BODY	WEIGHT
TYPE GT5	TOTAL 3900 /g

COMMENTS

FRONT	REAR
STEERING BLOCK COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	ANTI-ROLL BAR 1 2
C-HUB COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> X-HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>
FRONT ARM SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	UPRIGHT MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>
OFFSET 0 <input type="checkbox"/> +1 <input type="checkbox"/> +2 <input type="checkbox"/>	OFFSET STANDARD <input checked="" type="checkbox"/> +1 <input type="checkbox"/> +2 <input type="checkbox"/>
CASTER BUSHINGS +2° <input checked="" type="checkbox"/> +1° <input type="checkbox"/> 0° <input type="checkbox"/> -1° <input type="checkbox"/> -2° <input type="checkbox"/>	REAR DROOP 12
FRONT DROOP 10	
MEASURE UNDER WHEEL AXLE #10717 GAUGE	MEASURE UNDER WHEEL AXLE #10717 HUDY GAUGE

FRONT	REAR
BUMP STEER SHIM STEERING BLOCK 0 /mm STEERING PLATE 6 /mm SHIMS PLACE ALWAYS UNDER	WING HIGH 32 /mm
WHEELBASE SHIM POSITION 0 mm <input type="checkbox"/> 2 mm <input checked="" type="checkbox"/>	GRAPHITE BRACE WITHOUT <input type="checkbox"/> 1-PIECE <input type="checkbox"/> 2-PIECES <input checked="" type="checkbox"/>
SHIMS BEHIND FRONT ARM FF 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> FR 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>	REAR DIFFUSOR YES <input type="checkbox"/> NO <input type="checkbox"/>
SHIMS IN FRONT OF REAR ARM 2 mm <input type="checkbox"/> 4 mm <input checked="" type="checkbox"/>	WHEELBASE SHIM POSITION 2 mm <input type="checkbox"/> 4 mm <input checked="" type="checkbox"/>
LOWER ROLL CENTER ECCENTRIC BUSHINGS FRONT 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> REAR 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>	

FRONT	REAR
1.5 FRONT TOE OUT	2 REAR TOE IN
SERVO SAVER TIGHTEN <input checked="" type="checkbox"/> TIGHT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> SOFT <input type="checkbox"/>	WHEELBASE 0 mm <input type="checkbox"/> 1 mm <input type="checkbox"/> 2 mm <input type="checkbox"/> 3 mm <input type="checkbox"/> 4 mm <input checked="" type="checkbox"/>
ACKERMANN POSITION 3 2 1	SHIMS IN FRONT OF UPRIGHT
TOP DECK COMPOSITE <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	STANDARD BATTERY <input checked="" type="checkbox"/> BATTERY SETTING FRONT <input type="checkbox"/> REAR <input type="checkbox"/> SHORT BATTERY <input type="checkbox"/>

FRONT	REAR
2.25 FRONT CAMBER	2.5 REAR CAMBER
LENGTH 22.4 mm	LENGTH 22.4 mm
RIDE HEIGHT 10 /mm	RIDE HEIGHT 9 /mm