

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	2ª Prueba del Cto. Regional AECAR		
TRACK	Club CAPA		
NAME	David Pérez Pérez	DATE	18/09/2022

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP/TIME	LAPS	TIME
30	1	1	19.526 /sec	16	5:17.065

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE <input checked="" type="checkbox"/> YES		
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 5000 /cSt
PINION 47 /T	SPUR GEAR 99 /T	FINAL DRIVE RATIO 4.00

FRONT	SHOCKS	REAR
2.8	XRAY SPRINGS	2.7
350	OIL /cSt	350
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	PISTONS	3 HOLES <input type="checkbox"/>
<input type="checkbox"/> 4 HOLES	1.0mm	4 HOLES <input type="checkbox"/>
<input checked="" type="checkbox"/> PSS	1.1mm	PSS <input checked="" type="checkbox"/>
	1.2mm	
Ciego		Ciego

SHOCK LENGTH FRONT 9.5 /mm	SHOCK LENGTH REAR 9.5 /mm
----------------------------	---------------------------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
Matrix 36R	TIRES	Matrix 36R		
Sin aditivo	ADDITIVE	Sin aditivo		
	ADDITIVE TIMING			

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1335 /g	WEIGHT BALANCE	FRONT 51 %	REAR 49 %
MOTOR JUSTOCK 13.5	TIMING		
ESC JUSTOCK XR10	BATTERIES	RCProstyle 7500	
BODY Wolverine	WING	Wolverine Hard	

61 /mm	Dimension from body post to window bottom line	BODY POSITION
25 /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
		Dimension from edge to surface

COMMENTS

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER	TOE GAIN
Adjust with eccentric bushings	5 /mm	19 /mm	7 /mm		Adjust with eccentric bushings	6 /mm
1 /mm FF	5.0 /mm	FR 1 /mm	<input type="checkbox"/> SERVO SAVER		2.5 /mm RF	5.2 /mm
<input checked="" type="checkbox"/>	RIDE HEIGHT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> SERVO HORN		<input checked="" type="checkbox"/>	RR 2.5 /mm

2 /deg. CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>
	18 /mm	1 /mm SHIM 2 /mm	ALU <input type="checkbox"/>
		BULKHEAD SHIMS	SHIM 0.5 /mm
		YES <input type="checkbox"/> 3mm <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
		DRIVE SHAFT	
		58mm 59mm	
		STD. BEARING	
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
			5 /mm DOWNSTOP

2 /deg. CAMBER	BODY POST	REAR SUSPENSION	REAR HUB
Left = Right	VERTICAL <input checked="" type="checkbox"/>	0.5 /mm SHIM 2 /mm	COMPOSITE <input type="checkbox"/>
	HORIZONTAL <input type="checkbox"/>	REAR SHOCK POSITION	ALU <input type="checkbox"/>
		SHIM 1.5 /mm	
		DRIVE SHAFT	
		52mm 54mm	
		STD. BEARING	
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
			4 /mm DOWNSTOP

1 TOE OUT	ACKERMANN	SHIM	TOE IN
Left = Right	SHIM 0 /mm	/mm	Left = Right
DIFF POSITION	BRASS WEIGHT FOR MOTOR MOUNT		DIFF POSITION
UP <input type="checkbox"/>			UP <input type="checkbox"/>
DOWN <input checked="" type="checkbox"/>			DOWN <input checked="" type="checkbox"/>
UPPER ARM	STEERING BRIDGE	TOP DECK FLEX	UPPER ARM
STANDARD <input checked="" type="checkbox"/>	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	STANDARD <input checked="" type="checkbox"/>
		1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/>	
OFFSET	TOP DECK	TOP DECK CUTTING	OFFSET
STANDARD <input checked="" type="checkbox"/>	STANDARD		STANDARD <input checked="" type="checkbox"/>
-0.5mm <input type="checkbox"/>	<input checked="" type="checkbox"/> SPLITTED		-0.5mm <input type="checkbox"/>
SHIM/mm			SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 27 /deg.	T-BRACE
STEER. SHIM	ALU <input type="checkbox"/>
SIZE 0 /mm	BRASS <input type="checkbox"/>
FRONT BRACE	MOTOR MOUNT
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	CHASSIS T-BRACE
FR SERVO HOLDER	
	CHASSIS
	GRAPHITE <input checked="" type="checkbox"/>
	ALU <input type="checkbox"/>
	ALU FLEX <input type="checkbox"/>
FRONT ARMS	REAR ARMS
MEDIUM <input checked="" type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>
HARD <input type="checkbox"/>	HARD <input type="checkbox"/>
STEER. PLATE	
STANDARD <input checked="" type="checkbox"/>	
+1mm <input type="checkbox"/>	