

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	FinTrackTour round 4 21.5t				
TRACK	Äänekoski				
NAME	Janne Koivisto		DATE	1.10.22	

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
	2	1	/sec	/	

TRACK					
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT			
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST		
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH		

FRONT		TRANSMISSION		REAR	
SOLID AXLE	<input checked="" type="checkbox"/> YES				
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL	10k /cSt		
PINION	46 /T	SPUR GEAR	80 /T	FINAL DRIVE RATIO	3.30

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.5-2.8
400	OIL /cSt	400
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO
<input type="checkbox"/> 3 HOLES <input type="checkbox"/> 4 HOLES <input checked="" type="checkbox"/> PSS	PISTONS 1.0mm 1.1mm <input checked="" type="checkbox"/> 1.2mm	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
2x0.8mm		
SHOCK LENGTH FRONT		SHOCK LENGTH REAR
9 /mm		9 /mm

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Rush	TIRES	Rush
MG Black	ADDITIVE	MG Black
8	ADDITIVE TIMING	8

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1323 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
MOTOR	HW Justock 21.5t	TIMING		
ESC	HW XR10 ProStock	BATTERIES	Orca Infinite X 6090	
BODY	Wolverine 0.7mm	WING	BittyDesign Stock	

BODY POSITION

WING SIDE PLATE
YES ☒ NO ☐

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER <input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 5 /mm HEIGHT /mm SHIM 4 /mm	TOE GAIN 5.5 /mm
2 /mm FF 4.8 /mm FR 2 /mm <input checked="" type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> RIDE HEIGHT <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	2 /mm RF 5.0 /mm RR 2 /mm <input checked="" type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> RIDE HEIGHT <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

FRONT	REAR
CAMBER 2 /deg. Left=Right BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/> DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> STD. BEARING <input type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6.4 /mm DOWNSTOP	CAMBER 2 /deg. Left=Right BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/> FRONT SHOCK POSITION 1 /mm SHIM 2 /mm SHIM 0.5 /mm FRONT HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> SHOCK LENGTH 9 /mm SHOCK LENGTH REAR 9 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.8 /mm DOWNSTOP

FRONT TOP VIEW	REAR
TOE OUT 1 Left=Right ACKERMANN SHIM 0 /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> TOP DECK STANDARD <input type="checkbox"/> SPLITTED <input checked="" type="checkbox"/> TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK CUTTING	TOE IN 2.5 Left=Right SHIM 0.5 /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> TOP DECK STANDARD <input type="checkbox"/> SPLITTED <input checked="" type="checkbox"/> TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK CUTTING

FRONT BOTTOM VIEW	REAR
STEER. LOCK /deg. STEER. SHIM SIZE /mm FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> FR SERVO HOLDER FR RE FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/> REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>