

XRAY XB4'22

FRONT

APPLIED ☒ **APPLIED** ☒

ALU C-HUB SHIM
UP ☐ /mm
DOWN ☒ 2 /mm

LONGER BUSHINGS
UP ☐
DOWN ☐

DRIVE SHAFT
CVD ☐ ECS ☒
Lenght 83 /mm

SHIM
☐ mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐

LOWER SHOCK POSITION

DOWNSTOP mm

#107711 GAUGE

REAR UPRIGHT

DRIVE SHAFT
Lenght 77 /mm

SHIM
3 mm

SHIMS 2 /mm

HARD ☐
GRAPHITE ☒
ALU ☒

ROLL ENTER

1° ☒ **0.5°** ☐

#325341 ADJ. DRIVE AXLE

DOWNSTOP mm

#107711 GAUGE

FRONT

CASTER
6° ☐
7° ☒
9° ☐
12° ☐

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☒

WING CUTTING LINE
1 ☒ 2 ☐ 3 ☐ 4 ☐ 5 ☐

OFFSET 3 /slots

UPRIGHT WHEELBASE
SHIM 2 /mm

IN FRONT OF ARM

WING SIDE LINE
HIGHER ☐
LOWER ☒

WING POSITION
UP ☐
MIDDLE ☒
DOWN ☐

WING THICKNESS
☐ 0.75 ☒ 1 ☐ 1.5

TYPE Tec

FF ☒ 1° ☐ 0.5°
RF ☒ 1° ☐ 0.5°
FR ☒ 1° ☐ 0.5°
RR 2° ☒ 1° ☐ 0.5°

ROLL CENTER ECCENTRIC BUSHINGS

UP ☒ **DOWN** ☐

FRONT TOE
OUT ☐ IN ☒

ARM SHIM 2 mm

STEER. PLATE
HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER
SHIM 2 mm

Servo SAVER
SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL
STANDARD ☐
GRAPHITE ☒

REAR TOE
OUT ☐ IN ☒

GRAPHITE FOR REAR BRACE
YES ☒
NO ☐

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM 2 mm

FRONT CAMBER 1.5°

DOWNSTOP
SHIM 0 mm

LENGTH 22 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☒ -2mm ☐

FRONT DIFF HEIGHT
☒ ☐ ☐

RIDE HEIGHT 11 mm

#107720 GAUGE

REAR DIFF HEIGHT
☒ ☐ ☐ ☐ ☐ ☐

RIDE HEIGHT 11 mm

REAR CAMBER 2°

DOWNSTOP
SHIM 1 mm

LENGTH 28 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☐ -2mm ☒

FRONT ARMS
LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

BALANCE 0 g

SIDE GUARDS
HARD ☐
GRAPHITE ☒

BALANCE 0 g

REAR ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

T-BRACE

FRONT BATTERY POST

REAR BATTERY POST

BALANCE 0 g

BALANCE 0 g

CHASSIS FLEX
SCREW USED ☒
SCREW NOT USED ☐