

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	XRS Malaysia		
TRACK	SACC R/C Park		
NAME	Alexander Hagberg	DATE	13/11/2022

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
1	1	13.1 /sec	23	5:07

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 7000 /cSt
PINION 33 /T	SPUR GEAR 108 /T	FINAL DRIVE RATIO 6.2

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
400	OIL /cSt	425
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm			SHOCK LENGTH 8.5 /mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Rush VR3 36X	TIRES	Rush VR3 36X
MR33 V3	ADDITIVE	MR33 V3
10	ADDITIVE TIMING	10

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT 1330 /g	WEIGHT BALANCE	FRONT 49.5 %	REAR 50.5 %
----------------------	----------------	--------------	-------------

MOTOR	HW G4 13.5T	TIMING	
ESC	HW XR10 PRO G2S	BATTERIES	Sunpadow 6000
BODY	Wolverine 0.5	WING	Wolverine 0.5

66 /mm	Dimension from body post to window bottom line	BODY POSITION
6th hole /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
66 /mm	Dimension from edge to surface	

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'23		
X4'22	2.0mm	
X4'22	2.0mm	1.6mm
	NONE	BEARING

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm	UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm
2.75 /mm FF	5.0 /mm FR
5.0 /mm RIDE HEIGHT	2.75 /mm RR
<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN
TOE GAIN 5.5 /mm	3.0 /mm RF
	5.4 /mm RR
	3.0 /mm RIDE HEIGHT

2.0 /degr. CAMBER	BODY STOP YES <input checked="" type="checkbox"/> NO	FRONT SUSPENSION	0.5 /mm SHIM	3.0 /mm	FRONT HUB
Left = Right		FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	FRONT SHOCK POSITION		HARD <input checked="" type="checkbox"/>
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO			GRAPHITE <input type="checkbox"/>
		DRIVE SHAFT 58mm 59mm BEARING BLADE			ALU <input type="checkbox"/>
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.4 /mm	SHIM 0.5 /mm

2.0 /degr. CAMBER	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SUSPENSION	1.0 /mm SHIM	3.0 /mm	REAR HUB
Left = Right		REAR BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	REAR SHOCK POSITION		HARD <input checked="" type="checkbox"/>
		DRIVE SHAFT 52mm 54mm BEARING BLADE			GRAPHITE <input type="checkbox"/>
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4.2 /mm	ALU <input type="checkbox"/>

1.0 TOE OUT	ACKERMANN SHIM 0 /mm	FRONT TOP VIEW	2.5 TOE IN	SHIM 0 /mm	REAR
Left = Right		DIFF POSITION UP <input checked="" type="checkbox"/> DOWN	Left = Right		DIFF POSITION UP <input checked="" type="checkbox"/> DOWN
		UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD.			UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD.
		STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>			STEERING PLATE 8.0mm STD. <input checked="" type="checkbox"/> 7.5mm
		HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm			HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 27.5 /degr.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 7.0 /mm	MOTOR MOUNT
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/>
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>