

RACE	Czech Masters		
TRACK	Czech Masters		
NAME	Martin Bayer	DATE	21.1.2022

LAPS		BEST LAP TIME	
QUALIFYING POSITION	1	FINAL POSITION	1

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> VERY-LOW	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> VERY-HIGH
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input checked="" type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° <input type="checkbox"/> 90° <input checked="" type="checkbox"/> 120°	60° <input type="checkbox"/> 90° <input type="checkbox"/> 120°	60° <input type="checkbox"/> 90° <input type="checkbox"/> 120°
OIL <b>15K</b> cst	OIL	OIL <b>15K</b> cst

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
SLIPPING ADJUSTMENT	ONE-WAY TIGHTNESS
13 mm	1 CW TURN (BASIC SETUP)
<input type="checkbox"/> LOOSE	<input checked="" type="checkbox"/> FULLY TIGHTEN

GEARING	
PINION <b>19</b>	<b>78</b> CENTER DIFF SPUR

FRONT	SHOCKS	REAR
<b>5 dotz</b>	SPRINGS	<b>4 dotz</b>
cst <b>800</b>	OIL	cst <b>700</b>
REBOUND		
<input type="checkbox"/> 2 HOLES	PISTONS	<input type="checkbox"/> 2 HOLES
<input checked="" type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.2mm	<input checked="" type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.3mm	<input type="checkbox"/> 6 HOLES
	<input checked="" type="checkbox"/> ø1.4mm	
	<input type="checkbox"/> ø1.6mm	
	<input checked="" type="checkbox"/> ø1.7mm	
	CUSTOM PISTONS	
	ø 1.0 mm	ø 1.0 mm

FRONT	ANTI ROLL BAR	REAR
<b>2,0</b> mm	THICKNESS	<b>2,0</b> mm

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS		
MOTOR	<b>HW 5,5T</b>	<b>HW XR10 G2S</b>
MOTOR TIMING	<b>30</b>	<b>Sunapow</b>
BATTERY SIZE		SPEEDO
<input type="checkbox"/> STD. SHORT	<input checked="" type="checkbox"/> LOW SHORT	BATTERY

BODY	
TYPE	<b>Carpet</b>
	STANDARD <input type="checkbox"/> LIGHT <input checked="" type="checkbox"/>

COMMENTS	
<b>rear sus. holder wider</b>	

