

XRAY X4'23

FRONT

FRONT CASTER

5° ☒ 4° ☐ 3° ☐

Adjust with eccentric bushings

UPPER CLAMP

STD. ☒ ☐ -1.5mm

BUMP STEER

3 /mm

HEIGHT

/mm

SHIM

7 /mm

2 /mm **FF**

5 /mm **FR**

2 /mm **FR**

☐ **SERVO SAVER**

☒ **SERVO HORN**

TOE GAIN

5 /mm

2.5 /mm **RF**

5.2 /mm **RR**

2.5 /mm **RR**

REAR

REAR CASTER

0.5° ☐ 1.5° ☒ 2.5° ☐ 3.5° ☐ 4.5° ☐ 5.5° ☐

Adjust with eccentric bushings

UPPER CLAMP

STD. ☒ ☐ -1.5mm

TOE GAIN

5 /mm

2.5 /mm **RF**

5.2 /mm **RR**

2.5 /mm **RR**

FRONT

CAMBER

2 /deg. Left=Right

BODY STOP

YES ☒ NO ☐

11.5 /mm

FRONT BRACE

YES ☐ NO ☒

BULKHEAD SHIMS

YES ☒ 3mm ☐ NO ☐

DRIVE SHAFT

☒ 58mm ☐ 59mm ☒ **BEARING BLADE**

FRONT HUB

HARD ☐

GRAPHITE ☒

ALU ☐

SHIM

0.5 /mm

DOWNSTOP

5.4 /mm

REAR

CAMBER

2 /deg. Left=Right

BODY POST

VERTICAL ☐

HORIZONTAL ☒

DRIVE SHAFT

☐ 52mm ☒ 54mm ☒ **BEARING BLADE**

REAR HUB

HARD ☐

GRAPHITE ☒

ALU ☐

SHIM

1.5 /mm

DOWNSTOP

4 /mm

FRONT TOP VIEW

TOE OUT

1 /mm Left=Right

ACKERMANN

SHIM /mm

DIFF POSITION

UP ☐

DOWN ☒

UPPER ARM

SOFT ☒

MEDIUM STD. ☐

HUB OFFSET

STD. ☒ -0.5mm ☐ +0.5mm ☐ SHIM/mm

SHIM

/mm

STEERING PLATE

8.0mm ☒ STD. ☐

7.5mm ☐

STEERING BRIDGE

YES ☐ NO ☒

HUB OFFSET

STD. ☒ -0.5mm ☐ +0.5mm ☐ SHIM/mm

FRONT BOTTOM VIEW

STEER. LOCK

25 /deg.

STEER. SHIM

SIZE /mm

FRONT BRACE

YES ☐ NO ☒

SERVO HOLDER

FR ☐ RE ☐

FRONT ARMS

MEDIUM ☐

HARD ☒

T-BRACE

ALU ☐

BRASS ☐

CHASSIS

GRAPHITE ☐

ALU ☐

ALU FLEX ☒

REAR ARMS

MEDIUM ☐

HARD ☒