

XRAY XB4'23

FRONT

ALU C-HUB SHIM
UP 0 /mm
DOWN 2 /mm

LONGER BUSHINGS
UP ☐
DOWN ☐

DRIVE SHAFT
CVD ☒ ECS ☐
Length 83 /mm

SHIM
0 mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐

LOWER SHOCK POSITION

DOWNSTOP

#107711 GAUGE

APPLIED

REAR UPRIGHT

DRIVE SHAFT
Length 77 /mm

SHIM
3 mm

SHIMS
2 /mm

HARD GRAPHITE ALU HIGH ALU LOW
☐ ☐ ☒

ROLL ENTER

DOWNSTOP

#107711 GAUGE

CASTER
6° ☐
7° ☒
9° ☐
12° ☐

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☒

WING CUTTING LINE
1 2 3 4 5

OFFSET
2 /slots

BUMP STEER
SHIM 4 mm

WING SIDE LINE
HIGHER ☐
LOWER ☒

WING POSITION
UP ☐
MIDDLE ☒
DOWN ☐

WING THICKNESSES
0.75 ☐ 1 ☒ 1.5 ☐

TYPE TEC

FF

FR

RR

ROLL CENTER ECCENTRIC BUSHINGS
1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

UPRIGHT WHEELBASE
SHIM 2 /mm

IN FRONT OF ARM

FRONT TOE
OUT 1

ARM SHIM
2 mm

STEER. PLATE
HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER
SHIM 0 mm

Servo SAVER
SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL
STANDARD ☐
GRAPHITE ☒

REAR TOE
IN 0,5

GRAPHITE FOR REAR BRACE
YES ☒
NO ☐

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM
2 mm

FRONT CAMBER
2 °

DOWNSTOP
SHIM 2 mm

LENGTH
20 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☐ -2mm ☒

FRONT DIFF HEIGHT
☒ ☐ ☐

RIDE HEIGHT
12 mm

REAR DIFF HEIGHT
☒ ☐ ☐ ☐ ☐ ☐

RIDE HEIGHT
12 mm

REAR CAMBER
2 °

DOWNSTOP
SHIM 2 mm

LENGTH
27,5 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☐ -2mm ☒

FRONT ARMS
LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

BALANCE
g

MOTOR MOUNT
FRONT ☐ REAR ☐

T-BRACE

REAR ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

CHASSIS
ALU ☒
GRAPHITE ☐

SIDE GUARDS
HARD ☒
GRAPHITE ☐

BATTERY POSTS
FRONT BATTERY POST
REAR BATTERY POST

BALANCE
g

XRAY
35g

FRONT

REAR