

XRAY XB4'23

FRONT

APPLIED ☒ APPLIED

ALU C-HUB SHIM
UP ☒ /mm
DOWN ☒ /mm

LONGER BUSHINGS
UP ☐
DOWN ☐

DRIVE SHAFT
CVD ☒ ECS ☐
Length 83 /mm

SHIM
0 mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐

LOWER SHOCK POSITION

DOWNSTOP
#107711 GAUGE

REAR UPRIGHT

DRIVE SHAFT
Length 77 /mm

SHIM
2 mm

SHIMS
2 /mm

HARD GRAPHITE ALU HIGH ALU LOW
☐ ☐ ☒

ROLL ENTER

DOWNSTOP
#107711 GAUGE

CASTER
6° ☐
7° ☒
9° ☐
12° ☐

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☒

WING CUTTING LINE
1 2 3 4 5

WING SIDE LINE
HIGHER ☐
LOWER ☐

WING POSITION
UP ☒
MIDDLE ☐
DOWN ☐

WING THICKNESSES
0.75 ☐ 1 ☐ 1.5 ☐

TYPE

OFFSET
kit /slots

BUMP STEER
SHIM 0 mm

UPRIGHT WHEELBASE
SHIM 1 /mm

IN FRONT OF ARM

FF
☒ 1°
☐ 0.5°

RF
☒ 1°
☐ 0.5°

RR 2°
UP ☒ DOWN ☐

FRONT TOE
OUT ☒ IN ☐

REAR TOE
IN ☒ OUT ☐

STEER. PLATE
HARD ☐
GRAPHITE ☒
ALU ☐

BUMP STEER
SHIM 3 mm
SHIM UNDER STEER. PLATE

Servo Saver
SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL
STANDARD ☐
GRAPHITE ☒

GRAPHITE FOR REAR BRACE
YES ☐
NO ☒

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM
0 mm

ARM SHIM
2 mm

FRONT CAMBER
-2

FRONT DIFF HEIGHT
☒ ☐ ☐

REAR DIFF HEIGHT
☐ ☐ ☒ ☐ ☐

REAR CAMBER
-2

DOWNSTOP
SHIM mm

LENGTH
23 mm

UPSTOP
SHIM mm

COLLAR
STANDARD ☒ -2mm

RIDE HEIGHT
16 mm

RIDE HEIGHT
16 mm

FRONT ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

BALANCE
g

MOTOR MOUNT
FRONT ☒ REAR ☐

T-BRACE

CHASSIS
ALU ☒
GRAPHITE ☐

SIDE GUARDS
HARD ☒
GRAPHITE ☐

BATTERY POSTS
FRONT BATTERY POST
REAR BATTERY POST

BALANCE
g

BALANCE
g

FRONT

REAR