















RACE	Rumble In Rome			
TRACK	CRC			
NAME	Paul Ciccarello	DATE	06/12/2023	
TEMPERATURE AIR	82	TEMPERATURE TRACK		
LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH	
		/sec	/min	
TRACKS				
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT	
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH	
SURFACE	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY	
TYPE	<input checked="" type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY	
	<input type="checkbox"/> BLUE GROVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS	
CONDITION	<input type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WET	<input type="checkbox"/> MUD

DIFFERENTIAL					
FRONT		CENTER	REAR		
CASE MATERIAL				CASE MATERIAL	
OIL	7	8	4	OIL	
CROWN GEAR				CROWN GEAR	

GEARING			
MOTOR PINION	<input type="text"/>	<input type="text"/>	SPUR GEAR

FRONT	SHOCKS		REAR
emulsion	TYPE	emulsion	
5 dot	SPRINGS	4 dot	
	MEMBRANE		
500 /cst	OIL	500 /cst	
<input type="checkbox"/>  6 HOLES <input type="checkbox"/> <input type="checkbox"/>  8 HOLES <input type="checkbox"/> <input type="checkbox"/>  10 HOLES <input type="checkbox"/>	PISTONS 1.1 mm <input type="checkbox"/> 1.2 mm <input type="checkbox"/> 1.3 mm <input type="checkbox"/> 1.4 mm <input type="checkbox"/>	<input type="checkbox"/>  6 HOLES <input type="checkbox"/> <input type="checkbox"/>  8 HOLES <input type="checkbox"/> <input type="checkbox"/>  10 HOLES <input type="checkbox"/>	
 5-3 1.4/2 1.5	OTHER	5-3 1.5/2 1.6	
VALVE PISTONS			
5 + 2 HOLES  <input type="checkbox"/> 6 + 2 HOLES  <input type="checkbox"/> 8 + 2 HOLES  <input type="checkbox"/>	1.5 mm <input type="checkbox"/> 1.3 mm <input type="checkbox"/> 1.4 mm <input type="checkbox"/> 1.2 mm <input type="checkbox"/> 1.3 mm <input type="checkbox"/>	<input type="checkbox"/>  5 + 2 HOLES <input type="checkbox"/>  6 + 2 HOLES <input type="checkbox"/>  8 + 2 HOLES	

FRONT	ANTI-ROLL BAR	REAR
2.0 /mm	 THICKNESS	2.2 /mm

FRONT	TIRES		REAR
	BRAND		
	COMPOUND		
	INSERTS		
	WHEELS		

ELECTRONICS	
MOTOR	HW1900
SPEEDO	HW XR8 Plus
BATTERY TYPE	Factory xtreme

☐ STANDARD BATTERY

☐ SHORT BATTERY

☐ STANDARD BATTERY

FRONT
REAR

☐ SHORT BATTERY

BODY		OTHER	TOTAL WEIGHT
EASY	EASY LIGHT		
<input type="checkbox"/>	<input checked="" type="checkbox"/>		/g

batteries middle shorty

FRONT

STEERING BLOCK	
MEDIUM	<input type="checkbox"/>
HARD	<input type="checkbox"/>
GRAPHITE	<input checked="" type="checkbox"/>

UPPER ARM SHIM /mm				
<input type="checkbox"/> 0	<input checked="" type="checkbox"/> 1	<input type="checkbox"/> 1.5	<input type="checkbox"/> 2	<input type="checkbox"/>

PIVOT BALLS	
UP	STEEL <input type="checkbox"/> <input checked="" type="checkbox"/> ALU
DOWN	STEEL <input type="checkbox"/> <input checked="" type="checkbox"/> ALU

OFFSET		
0	+1	+2
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

PIVOT NUT	
ALU	<input checked="" type="checkbox"/>
BRASS	<input type="checkbox"/>

FRONT DROOP	
<input checked="" type="checkbox"/>	<input type="checkbox"/>

MEASURE UNDER WHEEL AXLE #107717 GAUGE

SHOCK TOWERS

FRONT	SHOCK TOWERS	REAR
ALU <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/>	ALU <input checked="" type="checkbox"/>

UPPER SHOCK POSITION

UPPER ARM WING

NONE	<input type="checkbox"/>
LEXAN	<input type="checkbox"/>
CARBON	<input checked="" type="checkbox"/>

FRONT LOWER SHOCK POSITION

LOWER ARM SHIM

<input checked="" type="checkbox"/>	<input type="checkbox"/>	
0	1mm	2mm

#107703 SUPPORT BLOCKS

REAR

ANTI-ROLL BAR

FLAT ☒ LSM ☐

UPRIGHT

MEDIUM	<input type="checkbox"/>
HARD	<input checked="" type="checkbox"/>
GRAPHITE	<input type="checkbox"/>
ALU	<input type="checkbox"/>

UPRIGHT ROLL CENTER

REAR ROLL CENTER

LOWER ROLL CENTER

REAR DROOP

OFFSET		
0	+1	+2
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

MEASURE UNDER WHEEL AXLE #107717 GAUGE

FRONT

UPPER ROLL CENTER

FRONT ☒ 1° ☐ 0.5°

TRAILING

STEERING BLOCK

FF

1° ☒ ☐ 0.5°

FR

1° ☒ ☐ 0.5°

LOWER ROLL CENTER

FRONT **REAR**

ECCENTRIC BUSHINGS

REAR

REAR WING

☐ COMPOSITE

☒ LEXAN

OTHER

☒ FRONT ☐ MIDDLE ☐ REAR

WING HOLDER

FRONT ☐

REAR ☒

RF

1° ☒ ☐ 0.5°

RR

1° ☒ ☐ 0.5°

CASTER SHIM

☐ ☒ ☐ ☐

0 1.0 1.0 2.0

UPPER ARM POSITION

BUMP STEER SHIM

STEERING PLATE 2 /mm

STEERING BLOCK /mm

SHIMS PLACE ALWAYS UNDER

WHEELBASE SHIM POSITION

☐ ☒ ☐

0mm 2mm 4mm

SHIMS BEHIND FRONT ARM

WHEELBASE SHIM POSITION

☐ ☐ ☒

0mm 2mm 4mm

SHIMS IN FRONT OF REAR ARM

CUT OUT HOLES

REDUCE DONORFORCE

GRAPHITE BRACE

WITHOUT ☐

1-PIECE ☐

2-PIECES ☒

INCREASE DONOR FORCE

YES ☐ **WICKERBILL PLATE** ☒ NO

3 FRONT TOE OUT

STEERING PLATE
1 DOTS ☐ 2 DOTS ☒

SERVO SAVER
TIGHT ☐
MEDIUM ☒
SOFT ☐

FRONT DRIVE SHAFT
CVD ☐
UNIVERSAL ☒
LENGTH /mm

TOP DECK
COMPOSITE ☒
GRAPHITE ☐

ACKERMANN POSITION
4 3 2 1

DRIVE SHAFT
CVD ☒
DOGBONE ☐

SIDE GUARD
SOFT ☐
MEDIUM ☒
GRAPHITE ☐

GRAPHITE BRACE
YES ☐ NO ☒

FRONT ☐ **BULKHEADS** ☒ **REAR** ☐

WHEELBASE
0 mm ☐ 1 mm ☐ 2 mm ☒ 3 mm ☐ 4 mm ☐
SHIMS IN FRONT OF UPRIGHT

3 REAR TOE IN

REAR DRIVE SHAFT
CVD ☐
UNIVERSAL ☒
LENGTH /mm

DRIVE SHAFT
CVD ☒
DOGBONE ☐

FRONT REAR

FRONT

FRONT CAMBER

LENGTH /mm

UPPER ARM

SOFT ☐

MEDIUM ☐

GRAPHITE ☒

LOWER ARM

SOFT ☐

MEDIUM ☐

GRAPHITE ☒

108 /mm

FULL TRAVEL SHOCKS LENGTH

124 /mm

REAR CAMBER

LENGTH /mm

FRONT DIFF HEIGHT

☐ ☐ ☒

REAR DIFF HEIGHT

☒ ☐ ☐

RIDE HEIGHT **22** /mm

26 /mm **RIDE HEIGHT**

#107717 RIDE HEIGHT GAUGE