

**XRAY X4'23**

### FRONT & REAR SUSPENSION

#### FRONT CASTER

Adjust with eccentric bushings

5° 4° 3°

☒ 5° ☐ 4° ☐ 3°

#### UPPER CLAMP

STD. ☐ ☐ -1.5mm

#### BUMP STEER

2.5 /mm

#### HEIGHT

std /mm

#### SHIM

7 /mm

2.5 /mm FF ☒ 5.2 /mm FR ☒ 2.5 /mm

☐ SERVO SAVER ☐ SERVO HORN

☒ RIDE HEIGHT ☐

TOE GAIN 5 /mm

3.0 /mm RF ☒ 5.2 /mm RR ☒ 3.0 /mm

☒ RIDE HEIGHT ☐

#### REAR CASTER

Adjust with eccentric bushings

0.5° 1.5° 2.5° 3.5° 4.5° 5.5°

☐ 0.5° ☐ 1.5° ☐ 2.5° ☐ 3.5° ☐ 4.5° ☐ 5.5°

#### UPPER CLAMP

STD. ☐ ☐ -1.5mm

### FRONT SUSPENSION

-2 /degr. CAMBER Left=Right

Left=Right

10.8 /mm

FRONT BRACE YES ☐ NO ☒

BULKHEAD SHIMS YES ☒ 3mm ☐ NO

DRIVE SHAFT ☒ 58mm ☐ 59mm ☒ BEARING ☐ BLADE

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.0 /mm DOWNSTOP

#### REAR HUB

HARD ☒ GRAPHITE ☐ ALU ☐

SHIM 0.5 /mm

### REAR SUSPENSION

-2 /degr. CAMBER Left=Right

Left=Right

2 /mm SHIM 3 /mm

REAR SHOCK POSITION 1 2

DRIVE SHAFT ☐ 52mm ☒ 54mm ☒ BEARING ☐ BLADE

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.0 /mm DOWNSTOP

#### REAR HUB

HARD ☒ GRAPHITE ☐ ALU ☐

SHIM 0.5 /mm

### FRONT TOP VIEW

+1 TOE OUT Left=Right

Left=Right

ACKERMANN SHIM 0.5 /mm

DIFF POSITION UP ☒ DOWN ☐

UPPER ARM SOFT ☒ MEDIUM STD. ☐

HUB OFFSET STD. ☒ -0.5mm ☐ +0.5mm SHIM/mm

### REAR TOP VIEW

-2 TOE IN Left=Right

Left=Right

SHIM 0 /mm

DIFF POSITION UP ☒ DOWN ☐

UPPER ARM SOFT ☒ MEDIUM STD. ☐

HUB OFFSET STD. ☒ -0.5mm ☐ +0.5mm SHIM/mm

### FRONT BOTTOM VIEW

STEER. LOCK /degr.

STEER. SHIM SIZE /mm

FRONT BRACE YES ☐ NO ☒

SERVO HOLDER FR RE

FRONT ARMS MEDIUM ☒ HARD ☐

### REAR BOTTOM VIEW

T-BRACE ALU ☐ BRASS ☐

CHASSIS T-BRACE

CHASSIS GRAPHITE ☒ ALU ☐ ALU FLEX ☐

REAR ARMS MEDIUM ☒ HARD ☐