

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Basic EU CARPET				
TRACK	Hudy Arena				
NAME	Martin Hudy		DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
		/sec	/		

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM
	<input type="checkbox"/> FAST	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
29 /T	110 /T	7K /St

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /Cst	350
25	REBOUND %	25
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH		SHOCK LENGTH	
8.5 /mm		8.5 /mm	

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

HUDY C3	TIRES	HUDY C3
HUDY RED	ADDITIVE	HUDY RED
8min	ADDITIVE TIMING	8min
	WIPE OFF TIME	
	TIRE WARMERS	
Timing:	Temp.:	Timing:
FRONT LEFT	FRONT RIGHT	REAR LEFT
		REAR RIGHT
TREATED AREA		

TOTAL WEIGHT	1320 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	---------	----------------	------------	-----------

MOTOR	5.0T	TIMING	35
ESC	HW	BATTERIES	
BODY	Twister	WING	Twister

67 /mm	Dimension from body post to window bottom line	BODY POSITION
7th hole +2mm	Dimension from body post to upper holder	WING SIDE PLATE
	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
65 /mm		

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'23	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm
	NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	

COMMENTS

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
5° 4° 3°	0.5° 1.5° 2.5° 3.5° 4.5° 5.5°
BUMP STEER	SHIM
2.0 /mm	4 /mm
HEIGHT	TOE GAIN
19 /mm	2.0 /mm
SHIM	2.5 /mm
4 /mm	5.2 /mm
2.0 /mm	RR 2.5 /mm
5.0 /mm	
FR 2.0 /mm	
<input checked="" type="checkbox"/> SERVO SAVER	
<input type="checkbox"/> SERVO HORN	

FRONT
2 /deg. CAMBER
Left = Right
BODY STOP
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
18.5 /mm
SHOCK HOLDERS
SHIM 4.0 /mm
SUSPENSION FLEX
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT
58mm 59mm BEARING BLADE
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge
DOWNSTOP

REAR
2 /deg. CAMBER
Left = Right
BODY POST
VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS
FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>
SHIM 4.0 /mm
SUSPENSION FLEX
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT
52mm 54mm BEARING BLADE
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge
DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT	3 TOE IN
Left = Right	Left = Right
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM 0.5 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
40g	BRASS WEIGHT FOR MOTOR MOUNT
12	40g
10	
DIFF POSITION	DIFF POSITION
<input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> +1mm	<input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM	UPPER ARM
SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM 0 /mm
HUB OFFSET	SHIM 7.5 /mm
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	PLATE <input checked="" type="checkbox"/> 8.0mm 7.5mm STD.

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
26 /deg.	ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
FR RE	MOTOR MOUNT
SERVO HOLDER	CHASSIS T-BRACE
FRONT ARMS	CHASSIS
MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input type="checkbox"/>
REAR ARMS	
MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	