

RACE	EOS r2		
TRACK	DAUN		
NAME	Bartek	DATE	06.02.2024
LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	3	FINAL POSITION	3

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH		
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 30 cSt	OIL cSt	OIL 20 cSt
SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
	SLIPPING 13 mm KIT <input type="checkbox"/> VENTILATED LOOSE 1 CW TURN (BASIC SETUP) FULLY TIGHTEN

GEARING	
PINION 18 1	81 1 SPUR GEAR

FRONT	SHOCKS	REAR
4	SPRINGS	4
cSt 400	OIL	cSt 350
REBOUND		
2 HOLES <input checked="" type="checkbox"/>	ø1.6mm <input type="checkbox"/> ø1.8mm <input checked="" type="checkbox"/>	2 HOLES <input checked="" type="checkbox"/>
HOLES <input type="checkbox"/> 2.0mm Precision <input type="checkbox"/> 2.5mm	PISTON THICKNESS <input checked="" type="checkbox"/> 2.0mm Precision <input type="checkbox"/> 2.5mm	HOLES <input type="checkbox"/> 2.0mm Precision <input type="checkbox"/> 2.5mm
KIT <input type="checkbox"/> 0mm ALU <input checked="" type="checkbox"/> -2mm -4mm	COLLAR <input checked="" type="checkbox"/> 0mm -2mm -4mm	KIT <input type="checkbox"/> 0mm ALU <input checked="" type="checkbox"/> -2mm -4mm
+4mm +2mm KIT	BALL JOINT <input checked="" type="checkbox"/>	KIT +2mm +4mm

FRONT	ANTI ROLL BAR	REAR
2 mm	THICKNESS	2 mm

FRONT	TIRES	REAR
eos	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS		
MOTOR HW 4.5	XR10prog2s	SPEEDO
MOTOR TIMING 30	Sp4600	BATTERY
BODY		TOTAL WEIGHT
Gamma 4dL	<input checked="" type="checkbox"/> LIGHT	/g
COMMENTS		

FRONT	APPLIED <input type="radio"/>	APPLIED <input checked="" type="checkbox"/>	REAR
-------	-------------------------------	---	------