

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Nantes Alternative				
TRACK	Nantes				
NAME			DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
		/sec		/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE		GEAR DIFF OIL	7k /cSt
PINION	44 /T	SPUR GEAR	96 /T	FINAL DRIVE RATIO	4.1

FRONT		SHOCKS		REAR	
2.5-5.8		XRAY SPRINGS		2.6	
350		OIL /cSt		350	
0		REBOUND %		0	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		FOAM INSERTS		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH		SHOCK LENGTH	
8.5 /mm		8.5 /mm	
1.1 THICKNESS/mm		1.2 THICKNESS/mm	

Rush 36x		TIRES		Rush 36x	
MR33 V3 Rouge		ADDITIVE		MR33 V3 Rouge	
20		ADDITIVE TIMING		20	
		WIPE OFF TIME			
Timing:		Temp.:		Timing:	
FRONT LEFT		FRONT RIGHT		REAR LEFT	
TREATED AREA		TREATED AREA		TREATED AREA	

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT %	REAR %
MOTOR	R1wurks 13.5 SS	TIMING	55	
ESC	R1wurks Digital3	BATTERIES	gensAce 6500	
BODY	Volverine	WING		

64 /mm	Dimension from body post to window bottom line	BODY POSITION
51 /mm	Dimension from edge to surface	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
2.0mm	<input type="checkbox"/> 1.6mm	
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>		

Droop Aerox AV 23.6 = 5.6 avec rondelle de 0.5mm
 Droop Aerox AR 22.6 = 4.4 avec rondelle de 0.5mm

Support de carro Arrière RCMaker

PareChoc 3D ae-rc.fr

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
3 /mm	6 /mm
HEIGHT	SHIM
19 /mm	6 /mm
2.5 /mm	5.2 /mm
FR 2.5 /mm	RR 3 /mm
<input type="checkbox"/> SERVO SAVER	<input type="checkbox"/> SERVO HORN
TOE GAIN	TOE IN
1.5 /mm	3 /mm
3 /mm	5.4 /mm
RF	RR
<input type="checkbox"/> MEDIUM	<input type="checkbox"/> MEDIUM
<input checked="" type="checkbox"/> HARD	<input checked="" type="checkbox"/> HARD
<input type="checkbox"/> GRAPHITE	<input type="checkbox"/> GRAPHITE
<input type="checkbox"/> ALU	<input type="checkbox"/> ALU

FRONT	
2 /deg.	CAMBER
Left = Right	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHOCK HOLDERS
14 /mm	SHIM 2 /mm
DRIVE SHAFT	SUSPENSION FLEX
58mm 59mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
<input checked="" type="checkbox"/> BEARING	<input checked="" type="checkbox"/> NO
<input checked="" type="checkbox"/> BLADE	<input type="checkbox"/> YES
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
23.6 /mm	DOWNSTOP

REAR	
2 /deg.	CAMBER
Left = Right	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHOCK HOLDERS
14 /mm	SHIM 2 /mm
DRIVE SHAFT	SUSPENSION FLEX
52mm 54mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
<input checked="" type="checkbox"/> BEARING	<input checked="" type="checkbox"/> NO
<input checked="" type="checkbox"/> BLADE	<input type="checkbox"/> YES
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
22.6 /mm	DOWNSTOP

FRONT TOP VIEW		REAR	
1	TOE OUT	2.75	TOE IN
Left = Right		Left = Right	
ACKERMANN	SHIM 0.5 /mm	SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
40g	BRASS WEIGHT FOR MOTOR MOUNT	40g	
DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING	SHIM 1 /mm
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW		REAR	
26 /deg.	STEER. LOCK	T-BRACE	ALU BRASS
FR RE	SERVO HOLDER	CHASSIS T-BRACE	
FRONT ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm <input type="checkbox"/>		GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm <input type="checkbox"/>	