

SET-UP SHEET

XRAY T4'20

RACE/TRACK	Skarpnäck	Base setup
NAME	Edwin Suneson	
DATE	2020-03-17	

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
		/sec	/	

TRACK

TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
---------------	---------------------------------	---

TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
--------------	------------------------------------	---	-------------------------------

TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
----------	------------------------------	--	-------------------------------

FRONT TRANSMISSION REAR

SOLID AXLE	<input checked="" type="checkbox"/> YES
------------	---

GEAR DIFFERENTIAL - OIL	/cst	GEAR DIFFERENTIAL - OIL	7000 /cst
-------------------------	------	-------------------------	-----------

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
29	110	7.2

FRONT SHOCKS REAR

ULTRA LOW PROFILE	<input checked="" type="checkbox"/> <input type="checkbox"/> SUPER LOW PROFILE	SHOCK TYPE	ULTRA LOW PROFILE	<input checked="" type="checkbox"/> <input type="checkbox"/> SUPER LOW PROFILE
-------------------	--	------------	-------------------	--

2.5-2.8	XRAY SPRINGS	2.6
---------	--------------	-----

450	OIL /cst	450
-----	----------	-----

REBOUND %	FOAM INSERTS
-----------	--------------

<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
---	---

<input type="checkbox"/> 3 HOLES	PISTONS	3 HOLES
----------------------------------	---------	---------

<input checked="" type="checkbox"/> 4 HOLES	1.0mm	<input checked="" type="checkbox"/> 4 HOLES
---	-------	---

<input type="checkbox"/> PSS	1.1mm	<input checked="" type="checkbox"/> PSS
------------------------------	-------	---

<input type="checkbox"/> PSS	1.2mm	<input type="checkbox"/> PSS
------------------------------	-------	------------------------------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Sweep	TIRES	Sweep
-------	-------	-------

Tire tweak	ADDITIVE	Tire tweak
------------	----------	------------

20	ADDITIVE TIMING	20
----	-----------------	----

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
------------	-------------	-----------	------------

TREATED AREA

FRONT	ROLL CENTER	REAR
-------	-------------	------

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

ARS - ACTIVE REAR SUSPENSION™

SHIM	SHIM	STEERING BLOCK
------	------	----------------

2 /mm	1 /mm	MEDIUM
-------	-------	--------

LINKS UP	HARD
----------	------

LINKS DOWN	GRAPHITE
------------	----------

SHIMS	0.5	ALU
-------	-----	-----

C-HUB	0°	2°	4°
-------	----	----	----

OFFSET	STANDARD
--------	----------

OFFSET	-0.75
--------	-------

MOTOR	HW 4.5t	TIMING	37.5
-------	---------	--------	------

ESC	HW	BATTERIES	Silverback 5800
-----	----	-----------	-----------------

BODY	DBX 0.5	WING	DBX Hard
------	---------	------	----------

COMMENTS

Tire warmers at 65 degrees

30g under receiver

FRONT	CASTER	0°	2°	4°	6°
-------	--------	----	----	----	----

SHIM	2	/mm
------	---	-----

SHIMS UNDER TOP DECK	/mm
----------------------	-----

WHEELBASE	/mm
-----------	-----

TOE OUT	1
---------	---

ACKERMANN	0.5	/mm
-----------	-----	-----

STEERING ARM	STANDARD
--------------	----------

STEERING PLATE	YES	NO
----------------	-----	----

FINAL TOE IN	2.5
--------------	-----

OUTBOARD + INBOARD TOE	OUTBOARD TOE
------------------------	--------------

SHIMS UNDER SHOCK	3	/mm
-------------------	---	-----

ROLL CENTER UPPER CLAMP	1	2
-------------------------	---	---

DIFF POSITION	UP	DOWN
---------------	----	------

BALANCE	10	/g
---------	----	----

BATT. BACKSTOP	COMPOSITE
----------------	-----------

BALANCE	12	/g
---------	----	----

ALU	ALU ADJ.	BRASS ADJ.
-----	----------	------------

STEERING SHIM	SHIM SIZE	6
---------------	-----------	---

BALANCE	10	/g
---------	----	----

SERVO HORN	SERVO SAVER	ALU
------------	-------------	-----

TOP DECK	2.0mm	1.6mm
----------	-------	-------

TOP DECK FLEX	NO POST	BEARING	BUSHING
---------------	---------	---------	---------

BALANCE	/g
---------	----

STEERING LOCK	29	/deg.
---------------	----	-------

CHASSIS BRACE	BRASS	ALU
---------------	-------	-----

SUSP. HOLDERS	FRONT	REAR
---------------	-------	------

SERVO HOLDER	FORWARD	STANDARD
--------------	---------	----------

MOTOR MOUNT	CHASSIS
-------------	---------

GRAPHITE	ALU	ALU-FLEX
----------	-----	----------

STEERING PLATE	8mm	8.5mm
----------------	-----	-------

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----

FF	FR	RR	RF
----	----	----	----