

XRAY XB4'21

FRONT

APPLIED ☒ NOT APPLIED

STEERING BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☒

LONGER BUSHINGS

UP ☒
DOWN ☐

SHIM

2 mm

DRIVE SHAFT

CVD ☐ ECS ☒
Length 83 /mm

ROLL ENTER

LOWER SHOCK POSITION

#107711 GAUGE

DOWNSTOP

mm

REAR UPRIGHT

DRIVE SHAFT

Length 75 /mm

SHIM

4 mm

SHIMS

2 /mm

HARD ☐
GRAPHITE ☐
ALU ☒

#325341 ADJ. DRIVE AXLE

1 2 3 4
1° ☒ 0.5°

DOWNSTOP

mm

#107711 GAUGE

CASTER

6° ☒
9° ☐
12° ☐

CASTER BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☒
ALU ☐

BUMP STEER

SHIM 2 mm

WING CUTTING LINE

1 2 3 4 5

OFFSET

Kit /slots

UPRIGHT WHEELBASE

SHIM 2 /mm

IN FRONT OF ARM

WING SIDE LINE

HIGHER ☐
LOWER ☒

WING POSITION

UP ☐
MIDDLE ☐
DOWN ☒

WING THICKNESS

0.75 ☐ 1 ☒ 1.5 ☐

TYPE Kit

FF

RF

FR

RR

1° ☒ 0.5° ☐
1° ☒ 0.5° ☐
1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

ROLL CENTER ECCENTRIC BUSHINGS

UP ☒ DOWN ☐

FRONT TOE

OUT 1

STEER. PLATE

HARD ☐
GRAPHITE ☒
ALU ☐

BUMP STEER

SHIM 5 mm

Servo SAVER

SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL

STANDARD ☐
GRAPHITE ☒

ARM SHIM

mm

REAR TOE

IN 1

GRAPHITE FOR REAR BRACE

YES ☒
NO ☐

REAR BRACE

MEDIUM ☐
HARD ☒

ARM SHIM

2 mm

FRONT CAMBER

2

DOWNSTOP

SHIM mm

LENGTH

mm

UPSTOP

SHIM 2 mm

COLLAR

STANDARD ☐ -2mm ☐

FRONT DIFF HEIGHT

RIDE HEIGHT 14 mm

REAR DIFF HEIGHT

RIDE HEIGHT 14 mm

REAR CAMBER

2

DOWNSTOP

SHIM 2 mm

LENGTH

mm

UPSTOP

SHIM 2 mm

COLLAR

STANDARD ☐ -2mm ☐

FRONT ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

T-BRACE

CHASSIS

STANDARD ☒
2.5mm ☐

REAR ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

CHASSIS FLEX

SCREW USED ☒
SCREW NOT USED ☐

SIDE GUARDS

MEDIUM ☐
HARD ☐
CF ☐

XRAY

35g

FRONT BALANCE

g

REAR BALANCE

g